







LOAD BEARING CAPACITY OF 40 KG.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

 $.XX = \pm .2$ [5.08] FRACTIONS $.XXX = \pm .02$ [.51] $\pm 1/32$ $.XXXX = \pm .005$ [.13] ANGLES $\pm 1^{\circ}$

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0

> ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY

PE PASTERNACK
an INFINIT® brand

Pasternack Enterprises, Inc. P.O.Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 | 1.866.727.8376 Fax: 1.949.261.7451

Website: www.pasternack.com E-mail: sales@pasternack.com THIRD-ANGLE PROJECTION



THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNACK CORPORATION ALL RIGHTS RESERVED.

SCALE N/A