

# 2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt



# **Power Dividers Technical Data Sheet**

**PE2067** 

### **Features**

- · 2-Way Power Divider
- · Resistive Design
- DC to 12.4 GHz Frequency Range

- Insertion Loss 6 dB Typ
- Max Power 1 Watt (CW)

# **Applications**

- Test and Measurement
- Military Communications
- Commercial Communications
- · Wireless Communications
- SATCOM

# Description

Pasternack carries a wide selection of power dividers to fit your needs. These components are essential in many systems, allowing the combination of multiple signals or splitting of a single signal into multiple signals with equal magnitude and phase. Pasternack's resistive and Wilkinson power dividers come with excellent performance featuring minimal loss, high isolation and low VSWR. They are available in both narrow and broad bandwidths with a variety of connector types such as 2.92mm, BNC, N and SMA.

The PE2067 is a 2-way resistive power divider that operates from DC to 12.4 GHz and can handle up to 1 Watt (CW) with 6 dB typ insertion loss. The package interface uses SMA connectors and is REACH and RoHS compliant.

# **Electrical Specifications**

Design Resistive

Number of Output Ports

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Impedance		50		Ohms
Input VSWR			1.2:1	
Insertion Loss		6		dB
Amplitude Balance		0.4		dB
Phase Balance		±2		Degrees
Input Power (CW)			1	Watts

Electrical Specification Notes: Insertion loss includes splitting loss.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt PE2067

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# 2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt



### **Power Dividers Technical Data Sheet**

**PE2067** 

#### **Mechanical Specifications**

Size

 Length
 0.5 in [12.7 mm]

 Width
 0.5 in [12.7 mm]

 Height
 0.38 in [9.65 mm]

 Weight
 0.041 lbs [18.6 g]

Configuration

Package Type Connectorized
Input Connector SMA Male
Input Connector Specification MIL-STD-348
Output Connectors SMA Female
Output Connectors Specification MIL-STD-348

**Environmental Specifications** 

Temperature

Operating Range -65 to +125 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant REACH Compliant

12/17/2015

### **Plotted and Other Data**

Notes:

2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt PE2067

URL: http://www.pasternack.com/2-way-sma-power-divider-dc-12.4-ghz-1-watts-pe2067-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

PE2067 CAD Drawing
2 Way SMA Resistive Power Divider From DC to 12.4 GHz Rated at 1 Watt

