



Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts

TECHNICAL DATA SHEET

PE2CP1018

Configuration

Connector 1	SMA Female
Connector 2	SMA Female
Coupled Connectors	SMA Female
Design	Dual Directional Coupler

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		6	GHz
Directivity	16			dB
Impedance		50		Ohms
Insertion Loss			0.35	dB
Input Power			100	Watts
Input VSWR			1.3:1	
Coupling Value		20		dB
Coupling Tolerance			± 1	dB
Coupling Flatness			±0.7	dB

Mechanical Specifications

Temperature

Operating Range +85 to -55 deg C

Size

Length 1.7 in [43.18 mm]
Width/Dia. 1.18 in [29.97 mm]
Height 0.55 in [13.97 mm]

Housing Material and Plating Aluminum Alloy, Chem Film

Connectors

Description	Connector 1	Connector 2	Coupled Connectors
Type	SMA Female	SMA Female	SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts PE2CP1018](#)



Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts

TECHNICAL DATA SHEET

PE2CP1018

Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts PE2CP1018](http://www.pasternack.com/dual-directional-20-db-sma-coupler-2-6-ghz-100-watts-pe2cp1018-p.aspx)

URL: <http://www.pasternack.com/dual-directional-20-db-sma-coupler-2-6-ghz-100-watts-pe2cp1018-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE2CP1018 CAD Drawing

Dual Directional 20 dB SMA Coupler From 2 GHz to 6 GHz Rated To 100 Watts



TOLERANCE	.XX ±.02
	.XXX ±.005
	ANG. ±1/2°

* THESE DIMENSIONS AND TOLERANCES SUPERSEDE NOTE #1 ON TITLE BLOCK.

INPUT	OUTPUT	FORWARD COUPLING	REFLECTED COUPLING	50 OHM LOAD
J1	J2	J4	J5	J3, J6
J2	J1	J5	J4	J3, J6

DWG TITLE

PE2CP1018

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

PE PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 041015

SCALE N/A

SIZE A

2233