

N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder

PE303-24



Configuration

- Connector 1: N Male
- Connector 2: N Male Right Angle
- Cable Type: 160 Series
- Coax Flex Type: Flexible

Features

- Max Frequency 18 GHz
- Shielding Effectivity > 100 dB
- 69.5% Phase Velocity
- Triple Shielded
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE303-24 type N male to type N male right angle 24 inch cable using 160 series coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to type N cable assembly has a male to male gender configuration with 50 ohm flexible 160 series coax. The PE303-24 type N male to type N male cable assembly operates to 18 GHz. The right angle type N interface on the 160 series cable allows for easier connections in tight spaces. The triple shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 100 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.4:1	
Velocity of Propagation		69.5		%
RF Shielding	100			dB
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Operating Voltage (AC)			1,200	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	2	6	10	14	16	GHz

N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder

PE303-24



Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
VSWR (Max.)	1.05:1	1.14:1	1.24:1	1.32:1	1.33:1	

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
VSWR (Max.)	1.34:1					

Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Amplitude Variation not to exceed 10% in a coiled vs uncoiled, a coil is defined as a 4% loop.

Mechanical Specifications

Cable Assembly

Width/Diameter	0.17 in [4.32 mm]
Weight	0.26 lbs [117.93 g]

Cable

Cable Type	160 Series
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	3
Shield Layer 1	Silver Plated Copper Tape
Shield Layer 2	Mylar Tape
Shield Layer 3	Silver Plated Copper Braid
Jacket Material	FEP, Blue
Jacket Diameter	0.163 in [4.14 mm]
One Time Minimum Bend Radius	1 in [25.4 mm]

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Male Right Angle
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Right Angle
Contact Material and Plating	Gold	Gold
Dielectric Type	PTFE	PTFE
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel
Coupling Nut Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel
Hex Size	13/16 in.	13/16 in.
Torque	15 in-lbs 1.7 Nm	15 in-lbs 1.7 Nm

N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder



PE303-24

Environmental Specifications

Operating Range Temperature

-48 to +204 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Values at 25°C, sea level.

Typical Performance Data

How to Order

Part Number Configuration:

PE303 **- xx** **uu**

└──────────┘ └──────────┘ └──────────┘

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number

Example: PE303-12 = 12 inches long cable
PE303-100cm = 100 cm long cable

N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder PE303-24](#)

URL: <https://www.pasternack.com/n-male-n-male-300-series-cable-assembly-pe303-24-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

N Male to N Male Right Angle Precision Cable 24 Inch Length Using 160 Series Coax, LF Solder



<div><div><div><div><div><div></div><div>PE</div></div><div><div>PASTERNAK®</div><div>THE ENGINEER'S RF SOURCE</div></div></div><div><div><div>Pasternack Enterprises, Inc.</div><div>P.O. Box 16759 Irvine CA 92623</div><div><div>Phone: (949) 261-1920 Fax: (949) 261-7451</div><div>Website: www.pasternack.com E-Mail: sales@pasternack.com</div></div></div></div></div></div></div>				DWG TITLE		
PE303			NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. 4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.			
FSCM NO. 53919	CAD FILE	111014	SCALE N/A	SIZE A	150	