

SMA Male to SMB Plug Cable 18 Inch Length Using RG142 Coax, RoHS



TECHNICAL DATA SHEET

PE3181LF-18

Configuration

Connector 1 SMA Male
Connector 2 SMB Plug
Cable Type RG142

Electrical Specifications

Frequency Range DC to 4 GHz Impedance 50 Ohms

Maximum VSWR 1.4:1

Velocity of Propagation 69.2 %

RF Shielding 90 dB

Mechanical Specifications

Temperature

Temperature Operating Range -65 to +165 deg C

Size

 Length
 18 in [457.2 mm]

 Weight
 0.065 lbs [29.48 g]

 Cable Color
 Tan

 One Time Minimum Bend Radius
 0.984 in [24.99 mm]

 Repeated Minimum Bend Radius
 2 in [50.8 mm]

Cable

Cable TypeRG142Inner Conductor TypeSolidCable Inner ConductorCopper Clad Steel, SilverNo of Shields2Dielectric TypePTFEJacket MaterialFEPJacket Diameter0.195 in [4.95 mm]

Connector 1

SMA Male Type Connector 1 Specification MIL-STD-348A Configuration Straight Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 50μ in. minimum Hex Size 5/16 in Torque 5 in-lbs [0.57 Nm] **Body Material and Plating** Brass, Nickel **Body Plating Specification** 100µ in. minimum

Dielectric Type Teflon

Connector 2

Type SMB Plug

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 18 Inch Length Using RG142 Coax, RoHS PE3181LF-18

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com







TECHNICAL DATA SHEET

PE3181LF-18

Connector 2 Specification
Configuration
Inner Conductor Plating Specification
Coupling Nut Plating Specification
Body Material and Plating
Body Plating Specification

MIL-STD-348A Straight 30µ in. minimum 100µ in. minimum Brass, Nickel 100µ in. minimum

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant REACH Compliant

12/19/2011

Plotted and Other Data

Notes:

• Values at +25 °C, sea level

SMA Male to SMB Plug Cable 18 Inch Length Using RG142 Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to SMB Plug Cable 18 Inch Length Using RG142 Coax, RoHS PE3181LF-18

URL: http://www.pasternack.com/sma-male-smb-plug-rg142bu-cable-assembly-pe3181lf-18-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PE3181LF-18 CAD DrawingSMA Male to SMB Plug Cable 18 Inch Length Using RG142 Coax, RoHS

