



SMA Male to SMA Male Precision Cable 60 Inch
Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE34286-60

SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

Configuration

Connector 1	SMA Male
Connector 2	SMA Male
Cable Type	150 Series

Electrical Specifications

Frequency Range, GHz	DC to 26.5
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,900

Typical Performance by Frequency

Frequency 1

Frequency, GHz	2
VSWR	1.05:1
Insertion Loss	0.17 dB/ft [0.56 dB/m]

Frequency 2

Frequency, GHz	6
VSWR	1.13:1
Insertion Loss	0.3 dB/ft [0.98 dB/m]

Frequency 3

Frequency, GHz	10
VSWR	1.11:1
Insertion Loss	0.4 dB/ft [1.31 dB/m]

Frequency 4

Frequency, GHz	14
VSWR	1.12:1
Insertion Loss	0.55 dB/ft [1.8 dB/m]

Frequency 5

Frequency, GHz	16
VSWR	1.19:1
Insertion Loss	0.6 dB/ft [1.97 dB/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE34286-60](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to SMA Male Precision Cable 60 Inch
Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE34286-60

Frequency 6

Frequency, GHz	18
VSWR	1.18:1
Insertion Loss	0.68 dB/ft [2.23 dB/m]

Frequency 7

Frequency, GHz	24
VSWR	1.22:1
Insertion Loss	0.85 dB/ft [2.79 dB/m]

Frequency 8

Frequency, GHz	26.5
VSWR	1.24:1
Insertion Loss	0.9 dB/ft [2.95 dB/m]

Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Mechanical Specifications

Cable Assembly

Cable Type	150 Series
------------	------------

Temperature

Temperature Operating Range, deg C	-50 to +205
------------------------------------	-------------

Size

Length, in [cm]	60 [152.4]
One Time Minimum Bend Radius, in [mm]	1 [25.4]

Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	1
Dielectric Type	PTFE
Jacket Material	FEP
Jacket Diameter, in [mm]	0.15 [3.81]

Connector 1

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE34286-60](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE34286-60

Body Material and Plating
Dielectric Type

Passivated Stainless Steel
PTFE

Connector 2

Type
Configuration
Inner Conductor Material and Plating
Coupling Nut Material and Plating
Hex Size, in.
Torque, in-lbs [Nm]
Body Material and Plating
Dielectric Type

SMA Male
Straight
Copper Clad Steel, Silver
Passivated Stainless Steel
5/16
8 [0.9]
Passivated Stainless Steel
PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level

SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS PE34286-60](http://www.pasternack.com/sma-male-sma-male-150-series-cable-assembly-pe34286-60-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-150-series-cable-assembly-pe34286-60-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE34286-60 CAD Drawing

SMA Male to SMA Male Precision Cable 60 Inch Length Using 150 Series Coax, RoHS



How To Order			
Part Number Configuration	Part # Ext.	Length In Inches	Length In Centimeters
PE3 zzz yy - xx uu	-12	12"	25Cm
	-24	24"	50Cm
	-36	36"	75Cm
	-48	48"	100Cm
	-60	60"	125Cm
	-XX	Custom Length	Custom Length



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE34286

- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].
 4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

FSCM NO. 53919

CAD FILE 030308

SCALE N/A

SIZE A

2233