



## SC Male to SC Male Cable Using RG225 Coax , LF Solder

### RF Cable Assemblies Technical Data Sheet

**PE34447LF**

#### Configuration

- Connector 1: SC Male
- Connector 2: SC Male
- Cable Type: RG225

#### Features

- Max Frequency 400 MHz
- Double Shielded
- PTFE (FG) Jacket

#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE34447LF SC male to SC male cable using RG225 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SC to SC cable assembly has a male to male gender configuration with 50 ohm flexible RG225 coax. The PE34447LF SC male to SC male cable assembly operates to 400 MHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

| Description                          | Minimum | Typical      | Maximum | Units        |
|--------------------------------------|---------|--------------|---------|--------------|
| Frequency Range                      | DC      |              | 400     | MHz          |
| VSWR                                 |         |              | 1.4:1   |              |
| Capacitance                          |         | 32.4 [106.3] |         | pF/ft [pF/m] |
| Dielectric Withstanding Voltage (AC) |         |              | 3,000   | Vrms         |

#### Specifications by Frequency

| Description           | F1    | F2    | F3    | F4 | F5 | Units |
|-----------------------|-------|-------|-------|----|----|-------|
| Frequency             | 50    | 100   | 250   |    |    | MHz   |
| Insertion Loss (Typ.) | 0.206 | 0.213 | 0.231 |    |    | dB/ft |
|                       | 0.68  | 0.7   | 0.76  |    |    | dB/m  |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable Using RG225 Coax , LF Solder PE34447LF](#)



## SC Male to SC Male Cable Using RG225 Coax , LF Solder

### RF Cable Assemblies Technical Data Sheet

**PE34447LF**

#### Mechanical Specifications

##### Cable Assembly

Weight 0.354 lbs [160.57 g]

##### Cable

Cable Type RG225  
Impedance 50 Ohms  
Inner Conductor Type Stranded  
Inner Conductor Material and Plating Copper, Silver  
Dielectric Type PTFE  
Number of Shields 2  
Shield Layer 1 Silver Plated Copper Braid  
Shield Layer 2 Silver Plated Copper Braid  
Jacket Material PTFE (FG), Brown  
Jacket Diameter 0.43 in [10.92 mm]

##### Connectors

| Description                   | Connector 1      | Connector 2      |
|-------------------------------|------------------|------------------|
| Type                          | SC Male          | SC Male          |
| Specification                 | MIL-STD-348A     | MIL-STD-348A     |
| Impedance                     | 50 Ohms          | 50 Ohms          |
| Contact Material and Plating  | Brass, Silver    | Brass, Silver    |
| Contact Plating Specification | 200µ in. minimum | 200µ in. minimum |
| Dielectric Type               | Teflon           | Teflon           |
| Body Material and Plating     | Brass, Nickel    | Brass, Nickel    |
| Body Plating Specification    | 100µ in. minimum | 100µ in. minimum |

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable Using RG225 Coax , LF Solder PE34447LF](#)



## SC Male to SC Male Cable Using RG225 Coax , LF Solder

### RF Cable Assemblies Technical Data Sheet

**PE34447LF**

#### How to Order

Part Number Configuration:

**PE34447LF**

- xx

uu

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE34447LF-12 = 12 inches long cable  
PE34447LF-100cm = 100 cm long cable

SC Male to SC Male Cable Using RG225 Coax , LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SC Male to SC Male Cable Using RG225 Coax , LF Solder PE34447LF](#)

URL: <https://www.pasternack.com/sc-male-sc-male-rg225u-cable-assembly-pe34447lf-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE34447LF CAD Drawing  
SC Male to SC Male Cable Using RG225 Coax , LF Solder

