



## SMA Male to SMA Male Cable Using PE-P141 Coax

### RF Cable Assemblies Technical Data Sheet

**PE350**

#### Configuration

- Connector 1: SMA Male
- Connector 2: SMA Male
- Cable Type: PE-P141

#### Features

- Max Frequency 26.5 GHz
- Shielding Effectivity > 110 dB
- 70% Phase Velocity
- Double Shielded
- FEP Jacket
- Highly durable flexible cable design with a VoP of 70%
- Thick wall SMA male connectors perform to 26.5 GHz
- Type N connectors perform to 18 GHz
- Electrical performance is equivalent to that of a solid wall 141 semi-rigid assembly
- Shielding effectiveness in excess of 100 dB
- Operating temperature range of -55 to +125°C
- RoHS Compliant
- Custom lengths built same-day
- 100% Continuity, Hi-Pot, and RF Tested

#### Applications

- General Purpose
- Laboratory Use

#### Description

PE-P141 high performance coax assemblies are cost effective designs, ideal for production test environments where rugged flexible cable assemblies are required. This series includes 26.5 GHz stainless steel SMA male connectors with a thick wall outer conductor designed to extend the life of the cable assemblies. A heavy-duty boot provides improved strain relief and adds to the durability of the cable assemblies. 18 GHz stainless steel type N male connectors with hex/knurl coupling nuts are also available. These cable assemblies are built using double-shielded flexible cable providing excellent shielding greater than 100 dB. All PE-P141 test cables are 100% continuity, Hi-Pot, and RF tested to the published specifications. Custom lengths are built to order and shipped the same day.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-P141 Coax PE350](#)



## SMA Male to SMA Male Cable Using PE-P141 Coax

### RF Cable Assemblies Technical Data Sheet

**PE350**

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR			1.45:1	
Velocity of Propagation		70		%
RF Shielding	110			dB
Capacitance		29.4 [96.46]		pF/ft [pF/m]

#### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	3	5	10	18	26.5	GHz
Insertion Loss (Typ.)	0.2	0.26	0.4	0.58	0.75	dB/ft
	0.66	0.85	1.31	1.9	2.46	dB/m

#### Electrical Specification Notes:

Insertion loss does not include the loss of the connectors.

Insertion loss is estimated as  $0.05 \times \sqrt{f(\text{GHz})}$  dB per connector.

Short lengths up to 12" long may exhibit VSWR measurements up to 9% higher.

Amplitude variation not to exceed 10% in a coiled vs uncoiled, a coil is defined as a 4% loop.

#### Mechanical Specifications

##### Cable Assembly

Weight 0.101 lbs [45.81 g]

##### Cable

Cable Type PE-P141  
 Impedance 50 Ohms  
 Inner Conductor Type Solid  
 Inner Conductor Material and Plating Copper Clad Steel, Silver  
 Dielectric Type PTFE  
 Number of Shields 2  
 Shield Layer 1 Silver Plated Copper Tape  
 Shield Layer 2 Silver Plated Copper Braid  
 Jacket Material FEP, Blue  
 Jacket Diameter 0.163 in [4.14 mm]  
 Repeated Minimum Bend Radius 0.8 in [20.32 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-P141 Coax PE350](#)



## SMA Male to SMA Male Cable Using PE-P141 Coax

### RF Cable Assemblies Technical Data Sheet

**PE350**

#### Connectors

Description	Connector 1	Connector 2
Type	SMA Male	SMA Male
Impedance	50 Ohms	50 Ohms
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel
Hex Size	5/16 inch	5/16 inch
Torque	8 in-lbs [0.9 Nm]	8 in-lbs [0.9 Nm]

#### Environmental Specifications

##### Temperature

Operating Range -55 to +125 deg C

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-P141 Coax PE350](#)



## SMA Male to SMA Male Cable Using PE-P141 Coax

### RF Cable Assemblies Technical Data Sheet

**PE350**

#### How to Order

Part Number Configuration:

**PE350**

- **xx**

**uu**

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE350-12 = 12 inches long cable  
PE350-100cm = 100 cm long cable

SMA Male to SMA Male Cable Using PE-P141 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Cable Using PE-P141 Coax PE350](#)

URL: <https://www.pasternack.com/sma-male-sma-male-pe-p141-cable-assembly-pe350-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE350 CAD Drawing  
SMA Male to SMA Male Cable Using PE-P141 Coax

REVISIONS		
REV.	DESCRIPTION	DATE
C	PCR PE350 20220613: EDITED NOTE 1, REMOVED "ONE AT EACH END 6"..."	06/21/2020
		SRAUTUS



UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:  
.X = ±.2 [5.08] FRACTIONS  
.XX = ±.02 [.51] ± 1/32  
.XXX = ±.005 [.13] ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:  
L ≤ 12 [305] = +1 [25] / -0  
12 [305] < L ≤ 60 [1524] = +2 [51] / -0  
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0  
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0  
300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN  
ARE FOR REFERENCE ONLY.

**PE PASTERNAK**  
an INFINITE brand

Pasternack Enterprises, Inc.  
P.O. Box 16759, Irvine, CA 92623.  
Phone: 1.949.261.1920 | 1.866.727.8376  
Fax: 1.949.261.7451  
Website: www.pasternack.com  
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND  
DESIGN IN THIS DOCUMENT  
IS THE PROPERTY OF  
PASTERNAK CORPORATION  
ALL RIGHTS RESERVED.

SHEET 1 OF 1  
SCALE N/A

SIZE A CAGE CODE 53919 DRAWN BY DMAY ITEM NO. PE350 REV C

NOTES:

1. CABLES 48" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 48" HAVE 2 LABELS.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.