



TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35423-48

TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS

Configuration

Connector 1	TNC Male
Connector 2	TNC Male
Cable Type	150 Series

Electrical Specifications

Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,900

Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Mechanical Specifications

Cable Assembly

Cable Type	150 Series
------------	------------

Temperature

Temperature Operating Range, deg C	-50 to +205
------------------------------------	-------------

Size

Length, in [cm]	48 [121.92]
One Time Minimum Bend Radius, in [mm]	1 [25.4]

Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	1
Dielectric Type	PTFE
Jacket Material	FEP
Jacket Diameter, in [mm]	0.15 [3.81]

Connector 1

Type	TNC Male
Configuration	Straight
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/8
Torque, in-lbs [Nm]	14 [1.58]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS PE35423-48](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35423-48

Body Material and Plating
Dielectric Type

Passivated Stainless Steel
PTFE

Connector 2

Type
Configuration
Inner Conductor Material and Plating
Coupling Nut Material and Plating
Hex Size, in.
Torque, in-lbs [Nm]
Body Material and Plating
Dielectric Type

TNC Male
Straight
Copper Clad Steel, Silver
Passivated Stainless Steel
5/8
14 [1.58]
Passivated Stainless Steel
PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level

TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS PE35423-48](http://www.pasternack.com/tnc-male-tnc-male-150-series-cable-assembly-pe35423-48-p.aspx)

URL: <http://www.pasternack.com/tnc-male-tnc-male-150-series-cable-assembly-pe35423-48-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE35423-48 CAD Drawing

TNC Male to TNC Male Precision Cable 48 Inch Length Using 150 Series Coax, RoHS



How To Order				Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
<u>Part Number Configuration</u>				<u>Examples</u>			
PE3 zzz yy - xx uu				-12	12"	-25CM	25Cm
				-24	24"	-50CM	50Cm
				-36	36"	-75CM	75Cm
				-48	48"	-100CM	100Cm
00 - 99999				-60	60"	-125CM	125Cm
LF = RoHS Compliant < Blank > = Standard				-xx	Custom Length	-xxCM	Custom Length
Note: LF applies only to RF cables							



PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE
PE35423

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS ± 1.5% OR 3/8", WHICHEVER IS GREATER.

FSCM NO. 53919

CAD FILE

030813

SCALE

N/A

SIZE

A

2233