



2.4mm Male to 2.4mm Male Precision Cable 72 Inch
Length Using 095 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35611-72

2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS

Configuration

Connector 1	2.4mm Male
Connector 2	2.4mm Male
Cable Type	095 Series

Electrical Specifications

Frequency Range, GHz	DC to 50
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,200

Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

Mechanical Specifications

Cable Assembly

Cable Type	095 Series
------------	------------

Temperature

Temperature Operating Range, deg C	-48 to +204
------------------------------------	-------------

Size

Length, in [cm]	72 [182.88]
One Time Minimum Bend Radius, in [mm]	1 [25.4]

Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	2
Dielectric Type	PTFE
Jacket Material	FEP
Jacket Diameter, in [mm]	0.095 [2.41]

Connector 1

Type	2.4mm Male
Configuration	Straight
Inner Conductor Material and Plating	Brass, Gold
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS PE35611-72](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS

TECHNICAL DATA SHEET

PE35611-72

Body Material and Plating
Dielectric Type

Passivated Stainless Steel
Noryl

Connector 2

Type
Configuration
Inner Conductor Material and Plating
Coupling Nut Material and Plating
Hex Size, in.
Torque, in-lbs [Nm]
Body Material and Plating
Dielectric Type

2.4mm Male
Straight
Brass, Gold
Passivated Stainless Steel
5/16
8 [0.9]
Passivated Stainless Steel
Noryl

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level

2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS PE35611-72](http://www.pasternack.com/2.4mm-male-2.4mm-male-095-series-cable-assembly-pe35611-72-p.aspx)

URL: <http://www.pasternack.com/2.4mm-male-2.4mm-male-095-series-cable-assembly-pe35611-72-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE35611-72 CAD Drawing

2.4mm Male to 2.4mm Male Precision Cable 72 Inch Length Using 095 Series Coax, RoHS



How To Order			Part # Ext.	Length In Inches	Part # Ext.	Length In Centimeters
Part Number Configuration		Examples	-12	12"	-25CM	25Cm
PE3	zzz	yy	-xx	uu	-50CM	50Cm
00 - 99999			-36	36"	-75CM	75Cm
LF = RoHS Compliant			-48	48"	-100CM	100Cm
< Blank > = Standard			-60	60"	-125CM	125Cm
Note: LF applies only to RF cables		CM = Centimeters < Blank > = Inches	-xx	Custom Length	-xxCM	Custom Length
		Length				

- NOTES:
- 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 - 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 - 3. DIMENSIONS ARE IN INCHES [mm].
 - 4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE
PE35611

FSCM NO. 53919

CAD FILE 100411

SCALE N/A

SIZE A

2233

PASTERNAK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com