

TNC Male Right Angle to TNC Male Cable Using RG223 Coax with HeatShrink, LF Solder




PE3680LF/HS

Configuration

- Connector 1: TNC Male Right Angle
- Connector 2: TNC Male
- Cable Type: RG223
- Coax Flex Type: Flexible

Features

- Max Frequency 3 GHz
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3680LF/HS TNC male right angle to TNC male cable using RG223 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack TNC to TNC cable assembly has a male to male gender configuration with 50 ohm flexible RG223 coax. The PE3680LF/HS TNC male to TNC male cable assembly operates to 3 GHz. The right angle TNC interface on the RG223 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Velocity of Propagation		66		%
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Operating Voltage (AC)			500	Vrms

Specifications by Frequency

TNC Male Right Angle to TNC Male Cable Using
RG223 Coax with HeatShrink, LF Solder



PE3680LF/HS

Part Number	Length	Description	F1	F2	F3	Units	Weight (lbs)
			Frequency			MHz	
PE3680LF/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.09	0.13	0.24	dB/ft	
			0.3	0.43	0.79	dB/m	
PE3680LF/HS-12	12 inch	Insertion Loss (Typ.)	0.39	0.43	0.54	dB	0.126
PE3680LF/HS-24	24 inch	Insertion Loss (Typ.)	0.48	0.56	0.78	dB	0.158
PE3680LF/HS-36	36 inch	Insertion Loss (Typ.)	0.57	0.69	1.02	dB	0.189
PE3680LF/HS-60	60 inch	Insertion Loss (Typ.)	0.75	0.95	1.5	dB	0.251
PE3680LF/HS-72	72 inch	Insertion Loss (Typ.)	0.84	1.08	1.74	dB	0.282

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1 dB
 Loss due to Connector 2: 0.2 dB
 Base Weight: 0.126 pounds
 Additional Weight per Inch: 0.00259 pounds

Mechanical Specifications

Cable Assembly

Weight 0.126 lbs [57.15 g]

Cable

Cable Type RG223
 Impedance 50 Ohms
 Inner Conductor Type Solid
 Inner Conductor Material and Plating Copper, Silver
 Dielectric Type PE
 Number of Shields 2
 Shield Layer 1 Silver Plated Copper Braid
 Shield Layer 2 Silver Plated Copper Braid
 Jacket Material PVC, Black
 Jacket Diameter 0.209 in [5.31 mm]
 Repeated Minimum Bend Radius 1 in [25.4 mm]

TNC Male Right Angle to TNC Male Cable Using
RG223 Coax with HeatShrink, LF Solder



PE3680LF/HS

Connectors

Description	Connector 1	Connector 2
Type	TNC Male Right Angle	TNC Male
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Configuration	Right Angle	Straight
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 µin minimum	30 µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 µin minimum	100 µin minimum
Coupling Nut Material and Plating	Brass, Nickel	Brass, Nickel
Coupling Nut Plating Specification	100 µin minimum	100 µin minimum

Environmental Specifications

Operating Range Temperature -40 to +80 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

TNC Male Right Angle to TNC Male Cable Using RG223 Coax with HeatShrink, LF Solder



PE3680LF/HS

Typical Performance Data

How to Order

Part Number Configuration:

PE3680LF/HS - xx uu

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number

Example: PE3680LF/HS-12 = 12 inches long cable
PE3680LF/HS-100cm = 100 cm long cable

TNC Male Right Angle to TNC Male Cable Using RG223 Coax with HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Right Angle to TNC Male Cable Using RG223 Coax with HeatShrink, LF Solder PE3680LF/HS](#)

URL: <https://www.pasternack.com/tnc-male-right-angle-to-tnc-male-cable-using-rg223-with-heatshrink-lf-solder-pe3680lf-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3680LF/HS CAD Drawing

TNC Male Right Angle to TNC Male Cable Using RG223 Coax with HeatShrink, LF Solder

