



C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE37910/HS

Configuration

- Connector 1: C Male Right Angle
- Connector 2: N Male
- Cable Type: RG8

Features

- 66% Phase Velocity
- PVC (NC) Jacket

Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE37910/HS type C male right angle to type N male cable using RG8 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type C to type N cable assembly has a male to male gender configuration with 50 ohm flexible RG8 coax. The right angle type C interface on the RG8 cable allows for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		66		%
Capacitance		30.8 [101.05]		pF/ft [pF/m]

Mechanical Specifications

Cable Assembly

Weight 0.317 lbs [143.79 g]

Cable

Cable Type RG8
Impedance 50 Ohms
Inner Conductor Type Stranded
Inner Conductor Material and Plating Copper
Dielectric Type PE
Number of Shields 1
Shield Layer 1 Copper Braid

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink PE37910/HS](#)



C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE37910/HS

Jacket Material
Jacket Diameter

PVC (NC), Black
0.405 in [10.29 mm]

Connectors

Description	Connector 1	Connector 2
Type	C Male Right Angle	N Male
Specification		MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating		Brass, Gold
Contact Plating Specification		30 µin minimum
Dielectric Type		PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification		100 µin minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100 µin minimum

Environmental Specifications

Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink PE37910/HS](#)



C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE37910/HS

How to Order

Part Number Configuration:

PE37910/HS

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE37910/HS-12 = 12 inches long cable
PE37910/HS-100cm = 100 cm long cable

C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink PE37910/HS](#)

URL: <https://www.pasternack.com/c-male-right-angle-to-n-male-cable-using-rg8-with-heatshrink-pe37910-hs-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE37910/HS CAD Drawing
C Male Right Angle to N Male Cable Using RG8 Coax with HeatShrink

