

MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink



RF Cable Assemblies Technical Data Sheet


PE39318/HS

Configuration

- Connector 1: MMCX Plug
- Connector 2: SMC Plug
- Cable Type: RG174

Features

- Max Frequency 1 GHz
- 66% Phase Velocity
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE39318/HS MMCX plug to SMC plug cable using RG174 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack MMCX to SMC cable assembly has a plug to plug gender configuration with 50 ohm flexible RG174 coax. The PE39318/HS MMCX plug to SMC plug cable assembly operates to 1 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink PE39318/HS](#)



MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE39318/HS

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1,000	MHz
VSWR			1.4:1	
Velocity of Propagation		66		%
Capacitance		31.08 [101.97]		pF/ft [pF/m]

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	50	100	250	500	1,000	MHz
Insertion Loss (Typ.)	0.066	0.084	0.137	0.211	0.32	dB/ft
	0.22	0.28	0.45	0.69	1.05	dB/m

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Weight 0.026 lbs [11.79 g]

Cable

Cable Type RG174
 Impedance 50 Ohms
 Inner Conductor Type Stranded
 Inner Conductor Material and Plating Copper Clad Steel
 Dielectric Type PE
 Number of Shields 1
 Shield Layer 1 Tinned Copper Braid
 Jacket Material PVC, Black
 Jacket Diameter 0.11 in [2.79 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink PE39318/HS](#)



MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE39318/HS

Connectors

Description	Connector 1	Connector 2
Type	MMCX Plug	SMC Plug
Specification	BS EN 122340	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Contact Plating Specification	30 µin minimum	30 µin minimum
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating	Brass, Gold	
Outer Conductor Plating Specification	3 µin minimum	
Body Material and Plating	Brass, Gold	Brass, Nickel
Body Plating Specification	3 µin minimum	100 µin minimum
Coupling Nut Material and Plating		Brass, Nickel
Coupling Nut Plating Specification		100 µin minimum
Hex Size		1/4 inch

Environmental Specifications

Temperature

Operating Range

-40 to +80 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink PE39318/HS](#)



MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE39318/HS

How to Order

Part Number Configuration:

PE39318/HS

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE39318/HS-12 = 12 inches long cable
PE39318/HS-100cm = 100 cm long cable

MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink PE39318/HS](#)

URL: <https://www.pasternack.com/mmcx-plug-to-smc-plug-cable-using-rg174-with-heatshrink-pe39318-hs-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE39318/HS CAD Drawing
MMCX Plug to SMC Plug Cable Using RG174 Coax with HeatShrink

