



N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet


PE3C0253

Configuration

- Connector 1: N Male
- Connector 2: SMA Male
- Cable Type: PE-P142LL

Features

- Max Frequency 18 GHz
- 80% Phase Velocity
- Triple Shielded
- Passivated Stainless Steel Jacket
- Type N Male to N Male and SMA Male to SMA Male Configurations Available
- Robust Connector/Armor Interface
- Low Loss Flexible Armored PE-P142LL Coax with Expanded PTFE Tape Dielectric
- Custom lengths available, call for pricing and lead time



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C0253 type N male to SMA male cable using PE-P142LL coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to SMA cable assembly has a male to male gender configuration with 50 ohm flexible PE-P142LL coax. The PE3C0253 type N male to SMA male cable assembly operates to 18 GHz. The triple shielding of this Pasternack cable assembly provides excellent shielding effectiveness. The durable stainless steel type N and SMA connectors and passivated stainless steel jacket of this cable assembly make it ideal anywhere a more rugged assembly is required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink PE3C0253](#)



N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C0253

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 18 | GHz |
| VSWR | | 1.25:1 | 1.35:1 | |
| Velocity of Propagation | | 80 | | % |

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|-----------------------|------|------|------|------|------|-------|
| Frequency | 1 | 3 | 5 | 10 | 18 | GHz |
| Insertion Loss (Typ.) | 0.08 | 0.14 | 0.18 | 0.25 | 0.36 | dB/ft |
| | 0.26 | 0.46 | 0.59 | 0.82 | 1.18 | dB/m |
| Power Handling (Max.) | | | | 220 | | W |

Electrical Specification Notes:

Insertion loss does not include the loss of the connectors.

Insertion loss is estimated as $0.05 \times \sqrt{f(\text{GHz})}$ dB per connector.

Mechanical Specifications

Cable Assembly

Cable

| | |
|--------------------------------------|----------------------------|
| Cable Type | PE-P142LL |
| Impedance | 50 Ohms |
| Inner Conductor Type | Solid |
| Inner Conductor Material and Plating | Copper, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 3 |
| Shield Layer 1 | Silver Plated Copper Braid |
| Shield Layer 2 | Aluminum Polyester |
| Shield Layer 3 | Silver Plated Copper Braid |
| Jacket Material | Passivated Stainless Steel |
| Jacket Diameter | 0.32 in [8.13 mm] |
| Repeated Minimum Bend Radius | 1 in [25.4 mm] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink PE3C0253](#)



N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C0253

Connectors

| Description | Connector 1 | Connector 2 |
|-----------------------------------|----------------------------|----------------------------|
| Type | N Male | SMA Male |
| Impedance | 50 Ohms | 50 Ohms |
| Contact Material and Plating | Brass, Gold | Brass, Gold |
| Body Material and Plating | Passivated Stainless Steel | Passivated Stainless Steel |
| Coupling Nut Material and Plating | Passivated Stainless Steel | Passivated Stainless Steel |

Environmental Specifications

Temperature

Operating Range -55 to +200 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink PE3C0253](#)



N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink

RF Cable Assemblies Technical Data Sheet

PE3C0253

How to Order

Part Number Configuration:

PE3C0253

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C0253-12 = 12 inches long cable
PE3C0253-100cm = 100 cm long cable

N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink PE3C0253](https://www.pasternack.com/n-male-sma-male-pe-p142ll-cable-assembly-pe3c0253-p.aspx)


URL: <https://www.pasternack.com/n-male-sma-male-pe-p142ll-cable-assembly-pe3c0253-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C0253 CAD Drawing

N Male to SMA Male Low Loss Cable Using PE-P142LL Coax with HeatShrink

| REVISIONS | | | |
|-----------|-----------------|----------|----------|
| REV. | DESCRIPTION | DATE | APPROVED |
| A | INITIAL RELEASE | 2/7/2020 | SELLIS |



| | | | | | | | |
|---|--|--|--|---|--|--|--|
| UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS | | | | THIRD-ANGLE PROJECTION | | | |
| TOLERANCES: | | | |  | | | |
| X = ± .2 [5.08] | | | | THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED. | | | |
| .XX = ± .02 [.51] | | | | SHEET 1 OF 1 | | | |
| .XXX = ± .005 [.13] | | | | SCALE N/A | | | |
| CABLE LENGTH (L) TOLERANCES: | | | | | | | |
| L ≤ 12 [305] = +1 [25] / -0 | | | | | | | |
| 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 | | | | | | | |
| 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 | | | | | | | |
| 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 | | | | | | | |
| 300 [7620] < L = +5% L / -0 | | | | | | | |
| ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | | | | REV A | | | |
| SIZE A CAGE CODE 53919 DRAWN BY K.DANG ITEM NO. PE3C0253 | | | | | | | |
| Pasternack Enterprises, Inc. P.O. Box 16759, Irvine, CA 92623. Phone: 1.949.261.1920 1.866.727.8376 Fax: 1.949.261.7451 Website: www.pasternack.com E-mail: sales@pasternack.com | | | | | | | |
|  | | | | | | | |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.