

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components




PE3C10278

Configuration

- Connector 1: BNC Male
- Connector 2: BNC Male
- Cable Type: LMR-240-LLPX

Features

- Max Frequency 4 GHz
- Shielding Effectivity > 90 dB
- 76% Phase Velocity
- Fluoropolymer Jacket
- 500 Mating Cycles



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C10278 BNC male to BNC male cable using LMR-240-LLPX coax is part of our full line of RF components available for same-day shipping. This Pasternack BNC to BNC cable assembly has a male to male gender configuration with 50 ohm LMR-240-LLPX coax. The PE3C10278 BNC male to BNC male cable assembly operates to 4 GHz.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
VSWR			1.4:1	
Velocity of Propagation		76		%
RF Shielding	90			dB
Capacitance		26.7 [87.6]		pF/ft [pF/m]
Inductance		0.067 [0.22]		uH/ft [uH/m]
DC Resistance Inner Conductor		4 [13.12]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		3.9 [12.8]		Ohms/1000ft [Ohms/Km]
Jacket Spark			5,000	Vrms

Specifications by Frequency

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components



PE3C10278

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency						
PE3C10278	Custom Lengths Available	Insertion Loss (Typ.)	0.023	0.038	0.056	0.079	0.163	dB/ft	
			0.08	0.13	0.19	0.26	0.54	dB/m	
PE3C10278-12	12 Inch	Insertion Loss (Typ.)	0.09	0.14	0.2	0.28	0.57	dB	0.235
PE3C10278-24	24 Inch	Insertion Loss (Typ.)	0.11	0.18	0.26	0.36	0.73	dB	0.271
PE3C10278-36	36 Inch	Insertion Loss (Typ.)	0.14	0.22	0.31	0.44	0.89	dB	0.306
PE3C10278-48	48 Inch	Insertion Loss (Typ.)	0.16	0.26	0.37	0.52	1.06	dB	0.341
PE3C10278-60	60 Inch	Insertion Loss (Typ.)	0.18	0.29	0.43	0.6	1.22	dB	0.376

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1: 0.1*SQRT(FGHz) dB
 Loss due to Connector 2: 0.1*SQRT(FGHz) dB
 Base Weight: 0.235 pounds
 Additional Weight per Inch: 0.4983 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter 0.5 in [12.7 mm]
 Weight 0.235 lbs [106.59 g]

Cable

Cable Type LMR-240-LLPX
 Impedance 50 Ohms
 Inner Conductor Material and Plating Copper
 Dielectric Type PTFE
 Outer Conductor 1 Material and Plating Aluminum Tape
 Jacket Material Fluoropolymer
 Jacket Diameter 0.214 in [5.44 mm]
 One Time Minimum Bend Radius 0.75 in [19.05 mm]
 Repeated Minimum Bend Radius 2.5 in [63.5 mm]
 Flat Plate Crush 85 lbs/in [1.52 Kg/mm]
 Tensile Strength 60 lbs [27.22 Kg]

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components



PE3C10278

Connectors

Description	Connector 1	Connector 2
Type	BNC Male	BNC Male
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Mating Cycles	500	500
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	50 µin minimum	50 µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Body Plating Specification	80 µin minimum	80 µin minimum

Environmental Specifications

Operating Range Temperature -40 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components



PE3C10278

Typical Performance Data

How to Order

Part Number Configuration:

PE3C10278

- **xx**

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE3C10278-12 = 12 inches long cable
PE3C10278-100cm = 100 cm long cable

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components PE3C10278](#)

URL: <https://www.pasternack.com/plenum-bnc-male-to-bnc-male-low-loss-cable-using-lmr-240-llpx-pe3c10278-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3C10278 CAD Drawing

Plenum BNC Male to BNC Male Low Loss Cable Using LMR-240-LLPX Coax with Times Microwave Components



NOTES:

1. CABLE ASSY LENGTH LABEL PLACEMENT: CABLES 84" OR LESS, ONE LABEL APPROX CENTERED, LONGER THAN 84 INCHES, TWO LABELS APPROX 12 INCHES FROM EACH CONNECTOR.
2. CABLE ASSEMBLY LENGTH DETERMINED BY ITEM PN AND DESCRIPTION.
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

PE DS Rev-04 Add2

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	06/21/2024	DZINN	AGANWANI

		INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 SCALE NONE SHEET 1 OF 1	
Website: www.Pasternack.com Phone: 1.866.727.8376 1.949.261.1920			
DESCRIPTION PLENUM CABLE ASSY, BNC MALE/BNC MALE, LMR-240-LLPX LOW LOSS COAX, TIMES MICROWAVE COMPONENTS			
SIZE	CAGE CODE	DRAWN BY	ITEM NO.
A	53919	DZINN	PE3C10278