

N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder

PE3C1093LF




Configuration

- Connector 1: N Male
- Connector 2: MMCX Plug Right Angle
- Cable Type: LMR-100A
- Coax Flex Type: Flexible

Features

- Max Frequency 1 GHz
- Shielding Effectivity > 90 dB
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C1093LF type N male to MMCX plug right angle cable using LMR-100 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to MMCX cable assembly has a male to plug gender configuration with 50 ohm flexible LMR-100A coax. The PE3C1093LF type N male to MMCX plug cable assembly operates to 1 GHz. The right angle MMCX interface on the LMR-100A cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		1	GHz
VSWR			1.4:1	
Velocity of Propagation		66		%
RF Shielding	90			dB
Group Delay		1.54 [5.05]		ns/ft [ns/m]
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Inductance		0.077 [0.25]		uH/ft [uH/m]
DC Resistance Inner Conductor		81 [265.75]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		9.5 [31.17]		Ohms/1000ft [Ohms/Km]

N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder



PE3C1093LF

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Jacket Spark			2,000	Vrms

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	50	100	250	500	1000	MHz	
PE3C1093LF	Custom Lengths Available	Insertion Loss (Typ.)	0.039	0.064	0.115	0.165	0.24	dB/ft	
			0.13	0.21	0.38	0.55	0.79	dB/m	
PE3C1093LF-24	24 In	Insertion Loss (Typ.)	0.38	0.43	0.53	0.63	0.78	dB	0.087
PE3C1093LF-36	36 In	Insertion Loss (Typ.)	0.42	0.5	0.65	0.8	1.02	dB	0.096
PE3C1093LF-48	48 In	Insertion Loss (Typ.)	0.46	0.56	0.76	0.96	1.26	dB	0.105
PE3C1093LF-100CM	100 CM	Insertion Loss (Typ.)	0.43	0.51	0.68	0.85	1.09	dB	0.099
PE3C1093LF-200CM	200 CM	Insertion Loss (Typ.)	0.56	0.72	1.06	1.39	1.88	dB	0.129

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.2 dB
Base Weight:	0.078 pounds
Additional Weight per Inch:	0.00075 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.078 lbs [35.38 g]

Cable

Cable Type	LMR-100A
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.11 in [2.79 mm]
One Time Minimum Bend Radius	0.25 in [6.35 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]
Bending Moment	0.1 lbs-ft [0.14 N-m]
Flat Plate Crush	10 lbs/in [0.18 Kg/mm]
Tensile Strength	15 lbs [6.8 Kg]

N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder



PE3C1093LF

Connectors

Description	Connector 1	Connector 2
Type	N Male	MMCX Plug Right Angle
Specification	MIL-STD-348A	BS EN 122340
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Right Angle
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 µin minimum	30 µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Gold
Body Plating Specification	100 µin minimum	3 µin minimum
Coupling Nut Material and Plating	Brass, Nickel	
Coupling Nut Plating Specification	100 µin minimum	

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder



PE3C1093LF

Typical Performance Data

How to Order

Part Number Configuration:

PE3C1093LF - xx uu

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number

Example: PE3C1093LF-12 = 12 inches long cable
PE3C1093LF-100cm = 100 cm long cable

N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder PE3C1093LF](#)

URL: <https://www.pasternack.com/n-male-to-mmxc-plug-low-loss-cable-using-lmr-100-lf-solder-pe3c1093lf-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3C1093LF CAD Drawing
N Male to MMCX Plug Right Angle Low Loss Cable Using LMR-100 Coax, LF Solder

