


SMA Male to Trimmed Lead Cable Using RG402 Coax




PE3C3559

Configuration

- Connector 1: SMA Male
- Connector 2: Trimmed Lead
- Cable Type: RG402
- Coax Flex Type: Semi-Rigid

Features

- 69.5% Phase Velocity



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3C3559 50 ohm SMA male to trimmed lead cable using RG402 coax is part of our full line of RF components available for same-day shipping. Pasternack's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		69.5		%

Mechanical Specifications


Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.04 lbs [18.14 g]

Cable

Cable Type	RG402
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Outer Conductor 1 Material and Plating	Copper
Jacket Material	Tan

SMA Male to Trimmed Lead Cable Using RG402 Coax



PE3C3559

One Time Minimum Bend Radius

0.25 in [6.35 mm]

Connectors

Description	Connector 1	Connector 2
Type	SMA Male	Trimmed Lead
Specification	MIL-STD-348A	
Impedance	50 Ohms	0 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	
Contact Plating Specification	50µ in. minimum	
Dielectric Type	Teflon	
Body Material and Plating	Stainless Steel, Gold	
Body Plating Specification	10µ in. minimum	
Coupling Nut Material and Plating	Brass, Nickel	
Coupling Nut Plating Specification	100µ in. minimum	
Hex Size	5/16 inch	
Torque	3 in-lbs 0.34 Nm	


Environmental Specifications

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

SMA Male to Trimmed Lead Cable Using RG402 Coax



PE3C3559

Typical Performance Data

How to Order

Part Number Configuration:

PE3C3559

- XX

uu

- Unit of Measure:
cm = Centimeters
<blank> = Inches

- Length

- Base Number

Example: PE3C3559-12 = 12 inches long cable
PE3C3559-100cm = 100 cm long cable

SMA Male to Trimmed Lead Cable Using RG402 Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to Trimmed Lead Cable Using RG402 Coax PE3C3559](#)

URL: <https://www.pasternack.com/sma-male-to-trimmed-lead-cable-using-rg402-pe3c3559-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3C3559 CAD Drawing
SMA Male to Trimmed Lead Cable Using RG402 Coax

