

## N Male to 7/16 DIN Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink, LF Solder




### PE3W03244LF/HS

#### Configuration

- Connector 1: N Male
- Connector 2: 7/16 DIN Male Right Angle
- Cable Type: LMR-400
- Coax Flex Type: Flexible

#### Features

- Max Frequency 3 GHz
- Shielding Effectivity > 90 dB
- 85% Phase Velocity
- Double Shielded
- PE Jacket



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3W03244LF/HS type N male to 7/16 DIN male right angle cable using LMR-400 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to 7/16 DIN cable assembly has a male to male gender configuration with 50 ohm flexible LMR-400 coax. The PE3W03244LF/HS type N male to 7/16 DIN male cable assembly operates to 3 GHz. The right angle 7/16 DIN interface on the LMR-400 cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Velocity of Propagation		85		%
RF Shielding	90			dB
Group Delay		1.2 [3.94]		ns/ft [ns/m]
Capacitance		23.9 [78.41]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor		1.39 [4.56]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		1.65 [5.41]		Ohms/1000ft [Ohms/Km]

N Male to 7/16 DIN Male Right Angle Low Loss Cable  
Using LMR-400 Coax with HeatShrink, LF Solder



**PE3W03244LF/HS**

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Jacket Spark			8,000	Vrms

**Specifications by Frequency**

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency					MHz	
PE3W03244LF/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.012	0.02	0.028	0.041	0.072	dB/ft	
			0.04	0.07	0.1	0.14	0.24	dB/m	
PE3W03244LF/HS-12	12 inch	Insertion Loss (Typ.)	0.17	0.17	0.18	0.2	0.23	dB	0.533
PE3W03244LF/HS-24	24 inch	Insertion Loss (Typ.)	0.18	0.19	0.21	0.24	0.3	dB	0.601
PE3W03244LF/HS-36	36 inch	Insertion Loss (Typ.)	0.19	0.21	0.24	0.28	0.37	dB	0.668
PE3W03244LF/HS-48	48 inch	Insertion Loss (Typ.)	0.2	0.23	0.27	0.32	0.44	dB	0.735
PE3W03244LF/HS-60	60 inch	Insertion Loss (Typ.)	0.21	0.25	0.29	0.36	0.51	dB	0.802

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.05 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.533 pounds
Additional Weight per Inch:	0.00559 pounds

**Mechanical Specifications**

**Cable Assembly**

Width/Diameter	0.5 in [12.7 mm]
Weight	0.54 lbs [244.94 g]

**Cable**

Cable Type	LMR-400
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PE, Black
Jacket Diameter	0.405 in [10.29 mm]
One Time Minimum Bend Radius	1 in [25.4 mm]
Repeated Minimum Bend Radius	4 in [101.6 mm]
Bending Moment	0.5 lbs-ft [0.68 N-m]
Flat Plate Crush	40 lbs/in [0.71 Kg/mm]
Tensile Strength	160 lbs [72.57 Kg]

N Male to 7/16 DIN Male Right Angle Low Loss Cable  
Using LMR-400 Coax with HeatShrink, LF Solder



## PE3W03244LF/HS

### Connectors

Description	Connector 1	Connector 2
Type	N Male	7/16 DIN Male Right Angle
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Right Angle
Contact Material and Plating	Beryllium Bronze, Gold	Spring Copper, Silver
Contact Plating Specification	50µ in. minimum	200µ In.
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Body Plating Specification	150µ in. minimum	150µ In.
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Plating Specification	150µ in. minimum	150µ In.
Hex Size	13/16 Inch	

### Environmental Specifications

Operating Range Temperature -40 to +85 deg C

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

N Male to 7/16 DIN Male Right Angle Low Loss Cable  
Using LMR-400 Coax with HeatShrink, LF Solder



**PE3W03244LF/HS**

**Typical Performance Data**

**How to Order**

Part Number Configuration:

**PE3W03244LF/HS - xx uu**



Example: PE3W03244LF/HS-12 = 12 inches long cable  
PE3W03244LF/HS-100cm = 100 cm long cable

N Male to 7/16 DIN Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to 7/16 DIN Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink, LF Solder PE3W03244LF/HS](#)

URL: <https://www.pasternack.com/n-male-to-7-16-din-male-low-loss-cable-using-lmr-400-with-heatshrink-lf-solder-pe3w03244lf-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3W03244LF/HS CAD Drawing

N Male to 7/16 DIN Male Right Angle Low Loss Cable Using LMR-400 Coax with HeatShrink, LF Solder

