

BNC Male to SMA Female Low Loss Cable Using LMR-240-UF Coax with HeatShrink



PE3W05157/HS

Configuration

- Connector 1: BNC Male
- Connector 2: SMA Female
- Cable Type: LMR-240-UF
- Coax Flex Type: Flexible

Features

- Max Frequency 4 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- TPE Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W05157/HS BNC male to SMA female cable using LMR-240-UF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to SMA cable assembly has a male to female gender configuration with 50 ohm flexible LMR-240-UF coax. The PE3W05157/HS BNC male to SMA female cable assembly operates to 4 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
VSWR			1.4:1	
Velocity of Propagation		84		%
RF Shielding	90			dB
Group Delay		1.21 [3.97]		ns/ft [ns/m]
Capacitance		24.2 [79.4]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor		4.28 [14.04]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		3.89 [12.76]		Ohms/1000ft [Ohms/Km]

BNC Male to SMA Female Low Loss Cable
Using LMR-240-UF Coax with HeatShrink



PE3W05157/HS

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Jacket Spark			5,000	Vrms

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency					MHz	
PE3W05157/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.028	0.046	0.066	0.095	0.193	dB/ft	
			0.1	0.16	0.22	0.32	0.64	dB/m	
PE3W05157/HS-12	12 In	Insertion Loss (Typ.)	0.23	0.25	0.27	0.3	0.4	dB	0.07
PE3W05157/HS-24	24 In	Insertion Loss (Typ.)	0.26	0.3	0.34	0.39	0.59	dB	0.103
PE3W05157/HS-36	36 In	Insertion Loss (Typ.)	0.29	0.34	0.4	0.49	0.78	dB	0.135
PE3W05157/HS-60	60 In	Insertion Loss (Typ.)	0.34	0.43	0.53	0.68	1.17	dB	0.199
PE3W05157/HS-300	300 In	Insertion Loss (Typ.)	0.9	1.35	1.85	2.58	5.03	dB	0.839

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.07 pounds
Additional Weight per Inch:	0.00267 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.259 lbs [117.48 g]

Cable

Cable Type	LMR-240-UF
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	TPE, Black
Jacket Diameter	0.24 in [6.1 mm]
One Time Minimum Bend Radius	0.75 in [19.05 mm]
Repeated Minimum Bend Radius	2.5 in [63.5 mm]
Bending Moment	0.13 lbs-ft [0.18 N-m]
Flat Plate Crush	13 lbs/in [0.23 Kg/mm]
Tensile Strength	80 lbs [36.29 Kg]

BNC Male to SMA Female Low Loss Cable
Using LMR-240-UF Coax with HeatShrink



PE3W05157/HS

Connectors

Description	Connector 1	Connector 2
Type	BNC Male	SMA Female
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	Beryllium Copper, Gold
Dielectric Type	POM	PTFE
Body Material and Plating	Brass, Nickel	Brass, Gold

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

BNC Male to SMA Female Low Loss Cable
Using LMR-240-UF Coax with HeatShrink



PE3W05157/HS

Typical Performance Data

How to Order

Part Number Configuration:

PE3W05157/HS - xx uu



Example: PE3W05157/HS-12 = 12 inches long cable
PE3W05157/HS-100cm = 100 cm long cable

BNC Male to SMA Female Low Loss Cable Using LMR-240-UF Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to SMA Female Low Loss Cable Using LMR®-240-UF Coax with HeatShrink PE3W05157/HS](#)

URL: <https://www.pasternack.com/bnc-male-to-sma-female-low-loss-cable-using-lmr-240-uf-with-heatshrink-pe3w05157-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W05157/HS CAD Drawing

BNC Male to SMA Female Low Loss Cable Using LMR-240-UF Coax with HeatShrink

