

## SMA Male Right Angle to N Male Low Loss Cable Using LMR-240-DB Coax with Times Microwave Components and HeatShrink, LF Solder




### PE3W16063LF/HS

#### Configuration

- Connector 1: SMA Male Right Angle
- Connector 2: N Male
- Cable Type: LMR-240-DB
- Coax Flex Type: Flexible

#### Features

- Max Frequency 6 GHz
- Shielding Effectivity > 90 dB
- 84% Phase Velocity
- Double Shielded
- PE Jacket



#### Applications

- General Purpose
- Laboratory Use

#### Description

Pasternack's PE3W16063LF/HS SMA male right angle to type N male cable using LMR-240-DB coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack SMA to type N cable assembly has a male to male gender configuration with 50 ohm flexible LMR-240-DB coax. The PE3W16063LF/HS SMA male to type N male cable assembly operates to 6 GHz. The right angle SMA interface on the LMR-240-DB cable allows for easier connections in tight spaces. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.4:1	
Velocity of Propagation		84		%
RF Shielding	90			dB
Group Delay		1.21 [3.97]		ns/ft [ns/m]
Capacitance		24.2 [79.4]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor		3.2 [10.5]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		3.89 [12.76]		Ohms/1000ft [Ohms/Km]

SMA Male Right Angle to N Male Low Loss Cable  
Using LMR-240-DB Coax with Times Microwave  
Components and HeatShrink, LF Solder



**PE3W16063LF/HS**

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Jacket Spark			5,000	Vrms

**Specifications by Frequency**

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency					MHz	
PE3W16063LF/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.039	0.055	0.079	0.129	0.204	dB/ft	
			0.13	0.19	0.26	0.43	0.67	dB/m	
PE3W16063LF/HS-12	12 Inch	Insertion Loss (Typ.)	0.39	0.41	0.43	0.48	0.56	dB	0.139
PE3W16063LF/HS-24	24 Inch	Insertion Loss (Typ.)	0.43	0.46	0.51	0.61	0.76	dB	0.173
PE3W16063LF/HS-36	36 Inch	Insertion Loss (Typ.)	0.47	0.52	0.59	0.74	0.97	dB	0.207
PE3W16063LF/HS-48	48 Inch	Insertion Loss (Typ.)	0.51	0.57	0.67	0.87	1.17	dB	0.241
PE3W16063LF/HS-60	60 Inch	Insertion Loss (Typ.)	0.55	0.63	0.75	1	1.37	dB	0.275

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.25 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.139 pounds
Additional Weight per Inch:	0.1075 pounds

**Mechanical Specifications**

**Cable Assembly**

Width/Diameter	0.5 in [12.7 mm]
Weight	0.139 lbs [63.05 g]

**Cable**

Cable Type	LMR-240-DB
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PE, Black
Jacket Diameter	0.24 in [6.1 mm]
One Time Minimum Bend Radius	0.75 in [19.05 mm]
Repeated Minimum Bend Radius	2.5 in [63.5 mm]
Bending Moment	0.25 lbs-ft [0.34 N-m]
Flat Plate Crush	20 lbs/in [0.36 Kg/mm]
Tensile Strength	80 lbs [36.29 Kg]

SMA Male Right Angle to N Male Low Loss Cable  
Using LMR-240-DB Coax with Times Microwave  
Components and HeatShrink, LF Solder



## PE3W16063LF/HS

### Connectors

Description	Connector 1	Connector 2
Type	SMA Male Right Angle	N Male
Specification		MIL-STD-348
Impedance	50 Ohms	50 Ohms
Configuration	Right Angle	Straight
Mating Cycles	500	
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	50 µin minimum	
Dielectric Type	PTFE	PTFE
Body Material and Plating	Passivated Stainless Steel	Brass, Tri-Metal
Coupling Nut Material and Plating	Passivated Stainless Steel	Brass, Tri-Metal
Torque	7 in-lbs 0.79 Nm	

### Environmental Specifications

Operating Range Temperature -40 to +85 deg C

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

SMA Male Right Angle to N Male Low Loss Cable Using LMR-240-DB Coax with Times Microwave Components and HeatShrink, LF Solder



**PE3W16063LF/HS**

**Typical Performance Data**

**How to Order**

Part Number Configuration:

**PE3W16063LF/HS - xx uu**



Example: PE3W16063LF/HS-12 = 12 inches long cable  
PE3W16063LF/HS-100cm = 100 cm long cable

SMA Male Right Angle to N Male Low Loss Cable Using LMR-240-DB Coax with Times Microwave Components and HeatShrink, LF Solder from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male Right Angle to N Male Low Loss Cable Using LMR-240-DB Coax with Times Microwave Components and HeatShrink, LF Solder PE3W16063LF/HS](#)

URL: <https://www.pasternack.com/sma-male-right-angle-to-n-male-low-loss-cable-using-lmr-240-db-and-heatshrink-lf-solder-pe3w16063lf-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

# PE3W16063LF/HS CAD Drawing

SMA Male Right Angle to N Male Low Loss Cable Using LMR-240-DB Coax with Times Microwave Components and HeatShrink, LF Solder



**PE PASTERNAK**  
an INFINITE brand

Website: [www.Pasternack.com](http://www.Pasternack.com)  
Phone: 1.866.727.8376 | 1.949.261.1920

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

SCALE: NONE  
SHEET: 1 OF 1

DESCRIPTION: SMA MALE RIGHT ANGLE TO N MALE CABLE USING LMR-240-DB COAX WITH HEATSHRINK, LF SOLDER

SIZE	A	CAGE CODE	53919	DRAWN BY	HBAKKE	ITEM NO.	PE3W16063LF/HS
REV	A						