

N Male to N Male Cable Using TCOM-600 Coax with HeatShrink




PE3W17373/HS

Configuration

- Connector 1: N Male
- Connector 2: N Male
- Cable Type: TCOM-600
- Coax Flex Type: Flexible

Features

- Max Frequency 6 GHz
- Shielding Effectivity > 100 dB
- 87% Phase Velocity
- Double Shielded
- PE Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W17373/HS type N male to type N male cable using TCOM-600 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack type N to type N cable assembly has a male to male gender configuration with 50 ohm flexible TCOM-600 coax. The PE3W17373/HS type N male to type N male cable assembly operates to 6 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 100 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.4:1	
Velocity of Propagation		87		%
RF Shielding	100			dB
Group Delay		1.17 [3.84]		ns/ft [ns/m]
Capacitance		23.4 [76.77]		pF/ft [pF/m]
Inductance		0.058 [0.19]		uH/ft [uH/m]
DC Resistance Inner Conductor		0.53 [1.74]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		1.52 [4.99]		Ohms/1000ft [Ohms/Km]



N Male to N Male Cable Using TCOM-600 Coax with HeatShrink

PE3W17373/HS

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Jacket Spark			8,000	Vrms

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency					MHz	
PE3W17373/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.012	0.018	0.027	0.046	0.077	dB/ft	
			0.04	0.06	0.09	0.16	0.26	dB/m	
PE3W17373/HS-6	6 inch	Insertion Loss (Typ.)	0.21	0.21	0.22	0.23	0.24	dB	0.3225
PE3W17373/HS-9	9 inch	Insertion Loss (Typ.)	0.21	0.22	0.23	0.24	0.26	dB	0.35675
PE3W17373/HS-12	12 inch	Insertion Loss (Typ.)	0.22	0.22	0.23	0.25	0.28	dB	0.391
PE3W17373/HS-18	18 inch	Insertion Loss (Typ.)	0.22	0.23	0.25	0.27	0.32	dB	0.4595
PE3W17373/HS-24	24 inch	Insertion Loss (Typ.)	0.23	0.24	0.26	0.3	0.36	dB	0.528

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.391 pounds
Additional Weight per Inch:	0.0114 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.81 in [20.57 mm]
Weight	0.391 lbs [177.35 g]

Cable

Cable Type	TCOM-600
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Tinned Copper Braid
Jacket Material	PE, Black
Jacket Diameter	0.59 in [14.99 mm]
One Time Minimum Bend Radius	1.5 in [38.1 mm]
Repeated Minimum Bend Radius	6 in [152.4 mm]
Bending Moment	2.75 lbs-ft [3.73 N-m]
Flat Plate Crush	60 lbs/in [1.07 Kg/mm]
Tensile Strength	350 lbs [158.76 Kg]

N Male to N Male Cable Using
TCOM-600 Coax with HeatShrink



PE3W17373/HS

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Male
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	50µin minimum	50µin minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Body Plating Specification	100µin minimum	100µin minimum
Coupling Nut Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Plating Specification	100µin minimum	100µin minimum
Hex Size	20.57 mm	20.57 mm
Torque	44 in-lbs 4.97 Nm	44 in-lbs 4.97 Nm

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

N Male to N Male Cable Using TCOM-600 Coax with HeatShrink



PE3W17373/HS

Typical Performance Data

How to Order

Part Number Configuration:

PE3W17373/HS - xx uu



Example: PE3W17373/HS-12 = 12 inches long cable
PE3W17373/HS-100cm = 100 cm long cable

N Male to N Male Cable Using TCOM-600 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to N Male Cable Using TCOM-600 Coax with HeatShrink PE3W17373/HS](#)

URL: <https://www.pasternack.com/n-male-to-n-male-cable-using-tcom-600-with-heatshrink-pe3w17373-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W17373/HS CAD Drawing

N Male to N Male Cable Using TCOM-600 Coax with HeatShrink

