

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax

PE3W17715





Configuration

- Connector 1: Smooth Bore Mini SMP Male
- Connector 2: Smooth Bore Mini SMP Male
- Cable Type: PE-P086HF
- Coax Flex Type: Flexible

Features

- Max Frequency 26.5 GHz
- 70% Phase Velocity
- Double Shielded
- FEP Jacket
- 500 Mating Cycles



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W17715 Mini SMP male smooth bore to Mini SMP male smooth bore cable using PE-P086HF coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack Mini SMP to Mini SMP cable assembly has a male to male gender configuration with 50 ohm flexible PE-P086HF coax. The PE3W17715 Mini SMP male to Mini SMP male cable assembly operates to 26.5 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR			1.4:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]

Specifications by Frequency

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax



PE3W17715

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
		Frequency	1000	2000	4500	9000	26500	MHz	
PE3W17715	Custom Lengths Available	Insertion Loss (Typ.)	0.192	0.277	0.429	0.631	1.18	dB/ft	
			0.63	0.91	1.41	2.08	3.88	dB/m	
PE3W17715-6	6 In	Insertion Loss (Typ.)	0.3	0.34	0.42	0.52	0.79	dB	0.01
PE3W17715-9	9 In	Insertion Loss (Typ.)	0.35	0.41	0.53	0.68	1.09	dB	0.013
PE3W17715-12	12 In	Insertion Loss (Typ.)	0.4	0.48	0.63	0.84	1.38	dB	0.017
PE3W17715-18	18 In	Insertion Loss (Typ.)	0.49	0.62	0.85	1.15	1.97	dB	0.023
PE3W17715-24	24 In	Insertion Loss (Typ.)	0.59	0.76	1.06	1.47	2.56	dB	0.03

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.0162 pounds
Additional Weight per Inch:	0.00109 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.017 lbs [7.71 g]

Cable

Cable Type	PE-P086HF
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Tape
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Blue
Jacket Diameter	0.104 in [2.64 mm]
One Time Minimum Bend Radius	0.52 in [13.21 mm]

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax



PE3W17715

Connectors

Description	Connector 1	Connector 2
Type	Mini SMP Male	Mini SMP Male
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Connection Method	Smooth Bore	Smooth Bore
Mating Cycles	500	500
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Contact Plating Specification	ASTM B488	ASTM B488
Dielectric Type	PTFE	PTFE
Body Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Body Plating Specification	ASTM B488	ASTM B488

Environmental Specifications

Operating Range Temperature -55 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax



PE3W17715

Typical Performance Data

How to Order

Part Number Configuration:

PE3W17715

- XX

uu

- Unit of Measure:

cm = Centimeters

<blank> = Inches

- Length

- Base Number

Example: PE3W17715-12 = 12 inches long cable
PE3W17715-100cm = 100 cm long cable

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax PE3W17715](#)

URL: <https://www.pasternack.com/smooth-bore-mini-smp-male-to-smooth-bore-mini-smp-male-vita-67.3-cable-using-pe-p086hf-pe3w17715-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W17715 CAD Drawing

Smooth Bore Mini SMP Male to Smooth Bore Mini SMP Male VITA 67.3 Cable Using PE-P086HF Coax

