

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink



PE3W18543/HS

Configuration

- Connector 1: BNC Male
- Connector 2: FAKRA Jack
- Cable Type: LMR-100A
- Coax Flex Type: Flexible

Features

- Max Frequency 4 GHz
- Shielding Effectivity > 90 dB
- 66% Phase Velocity
- Double Shielded
- PVC Jacket



Applications

- General Purpose
- Laboratory Use

Description

Pasternack's PE3W18543/HS BNC male to water blue FAKRA jack cable using LMR-100 coax is part of our full line of RF components available for same-day shipping. Pasternack's flexible RF cable assemblies are ideal for applications where tight bends and flexure are required. This Pasternack BNC to FAKRA cable assembly has a male to jack gender configuration with 50 ohm flexible LMR-100A coax. The PE3W18543/HS BNC male to FAKRA jack cable assembly operates to 4 GHz. The double shielding of this Pasternack cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other available RF cable assembly value added services include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
VSWR			1.4:1	
Velocity of Propagation		66		%
RF Shielding	90			dB
Group Delay		1.54 [5.05]		ns/ft [ns/m]
Capacitance		30.8 [101.05]		pF/ft [pF/m]
Inductance		0.077 [0.25]		uH/ft [uH/m]
DC Resistance Inner Conductor		81 [265.75]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		9.5 [31.17]		Ohms/1000ft [Ohms/Km]

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink



PE3W18543/HS

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Jacket Spark			2,000	Vrms

Specifications by Frequency

Part Number	Length	Description	F1	F2	F3	F4	F5	Units	Weight (lbs)
			Frequency					MHz	
PE3W18543/HS	Custom Lengths Available	Insertion Loss (Typ.)	0.064	0.115	0.165	0.24	0.502	dB/ft	
			0.21	0.38	0.55	0.79	1.65	dB/m	
PE3W18543/HS-24	24 In	Insertion Loss (Typ.)	0.33	0.43	0.53	0.68	1.21	dB	0.067
PE3W18543/HS-36	36 In	Insertion Loss (Typ.)	0.4	0.55	0.7	0.92	1.71	dB	0.076
PE3W18543/HS-48	48 In	Insertion Loss (Typ.)	0.46	0.66	0.86	1.16	2.21	dB	0.085
PE3W18543/HS-100CM	100 CM	Insertion Loss (Typ.)	0.41	0.58	0.75	0.99	1.85	dB	0.079
PE3W18543/HS-200CM	200 CM	Insertion Loss (Typ.)	0.62	0.96	1.29	1.78	3.5	dB	0.109

The insertion loss data for the base model does not include loss due to the connectors. Each length includes insertion loss due to the connectors.

Loss due to Connector 1:	0.1 dB
Loss due to Connector 2:	0.1 dB
Base Weight:	0.058 pounds
Additional Weight per Inch:	0.00075 pounds

Mechanical Specifications

Cable Assembly

Width/Diameter	0.5 in [12.7 mm]
Weight	0.049 lbs [22.23 g]

Cable

Cable Type	LMR-100A
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Steel
Dielectric Type	PE
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PVC, Black
Jacket Diameter	0.11 in [2.79 mm]
One Time Minimum Bend Radius	0.25 in [6.35 mm]
Repeated Minimum Bend Radius	1 in [25.4 mm]
Bending Moment	0.1 lbs-ft [0.14 N-m]
Flat Plate Crush	10 lbs/in [0.18 Kg/mm]
Tensile Strength	15 lbs [6.8 Kg]

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink



PE3W18543/HS

Connectors

Description	Connector 1	Connector 2
Type	BNC Male	FAKRA Jack
Specification	MIL-STD-348A	
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Color		WB
Mating Cycles	500	
Contact Material and Plating	Brass, Gold	Phosphor Bronze, Gold
Contact Plating Specification	30 µin minimum	
Dielectric Type	PTFE	PTFE
Outer Conductor Material and Plating		Brass, Nickel
Body Material and Plating	Brass, Nickel	Plastic
Body Plating Specification	100 µin minimum	
Coupling Nut Material and Plating	Brass, Nickel	

Environmental Specifications

Operating Range Temperature -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink



PE3W18543/HS

Typical Performance Data

How to Order

Part Number Configuration:

PE3W18543/HS - xx uu

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number

Example: PE3W18543/HS-12 = 12 inches long cable
PE3W18543/HS-100cm = 100 cm long cable

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink PE3W18543/HS](#)

URL: <https://www.pasternack.com/bnc-male-to-fakra-jack-low-loss-cable-using-lmr-100-with-heatshrink-pe3w18543-hs-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE3W18543/HS CAD Drawing

BNC Male to Water Blue FAKRA Jack Low Loss Cable Using LMR-100 Coax with HeatShrink

