

# N Female Bulkhead Mount Connector Crimp/Solder Attachment for LMR-200, PE-C200, IP67 Rated



## PE45047

## Configuration

- N Female Connector
- IFC 61169-16
- 50 Ohms
- · Straight Body Geometry

#### **Features**

- · Max. Operating Frequency 3 GHz
- Excellent VSWR of 1.2:1
- · Silver Plated Copper Contact

## **Applications**

- · General Purpose Test
- · Rack and Panel Mount Applications

- Crimp/Solder Method
- Connector Interface Types: LMR-200, PE-C200
- Bulkhead
- · 2-Jan inch Hex
- · 5 µm minimum contact plating
- IP67 Rated
- Custom Cable Assemblies

## **Description**

Pasternack's PE45047 type N, N, Standard, Connector is part of our full line of RF components available for same-day shipping. Our type N female connector operates up to a maximum frequency of 3 GHz and offers excellent VSWR of 1.2:1. This type N bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The connector has an IP67 rating to protect against dust and temporary moisture protection under immersion conditions.

Our type N female bulkhead connector PE45047 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

## **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.2:1	
Insertion Loss			0.1	dB
Operating Voltage (AC)			2,500	Vrms
Dielectric Withstanding Voltage (AC)			1,700	Vrms
Inner Conductor DC Resistance			0.8	mOhms
Outer Conductor DC Resistance			0.4	mOhms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

## **Mechanical Specifications**

Size

 Length
 1.66 in [42.16 mm]

 Width
 0.86 in [21.84 mm]



# N Female Bulkhead Mount Connector Crimp/Solder Attachment for LMR-200, PE-C200, IP67 Rated



## PE45047

Weight 0.115 lbs [52.16 g]
Mating Cycles 500 Cycles

## **Material Specifications**

Description	Material	Plating	
Contact	Copper	Silver	
		5 µm minimum	
Insulation	PTFE	PTFE	
Outer Conductor	Brass	Tri-Metal	
		2 µm minimum	

### **Environmental Specifications**

#### **Temperature**

Operating Range -40 to 85 deg C
Ingress Protection (IP) Rating IP67 Rated
Shock IEC 60068-2-27
Vibration IEC 60068-2-6-Fc
Thermal Shock IEC 60068-2-14-Na

Environmental Specification Notes: Weather standard: IEC 60068 40/085/21

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

N Female Bulkhead Mount Connector Crimp/Solder Attachment for LMR-200, PE-C200, IP67 Rated from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Bulkhead Mount Connector Crimp/Solder Attachment for LMR-200, PE-C200, IP67 Rated PE45047

URL: https://www.pasternack.com/n-female-Imr-200-pe-c200-connector-pe45047-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

