

C Male Connector Clamp/Solder Attachment for RG59, RG62, RG71



# **RF Connectors Technical Data Sheet**

PE4952

# Configuration

- C Male Connector
- MIL-STD-348
- 50 Ohms

- Straight Body Geometry
- RG59, RG62, RG71 Interface Type
- Clamp/Solder Attachment

#### **Features**

Silver Plated Contact

Contact plating according to QQ-S-365

# **Applications**

• General Purpose Test

Custom Cable Assemblies

## Description

Pasternack's PE4952 type C male connector with clamp/solder attachment for RG59, RG62 and RG71 is part of our full line of RF components available for same-day shipping.

Our type C male connector PE4952 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

#### **Mechanical Specifications**

Size

 Length
 1.37 in [34.8 mm]

 Width/Dia.
 0.75 in [19.05 mm]

 Weight
 0.082 lbs [37.19 g]

#### **Material Specifications**

| Description  | Material | Plating            |  |
|--------------|----------|--------------------|--|
| Contact      |          | Silver<br>QQ-S-365 |  |
| Insulation   | PTFE     |                    |  |
| Body         | Brass    | Nickel<br>QQ-N-290 |  |
| Coupling Nut | Brass    | Nickel<br>QQ-N-290 |  |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: C Male Connector Clamp/Solder Attachment for RG59, RG62, RG71 PE4952

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# C Male Connector Clamp/Solder Attachment for RG59, RG62, RG71



### **RF Connectors Technical Data Sheet**

PE4952

Environmental Specifications Temperature

**Operating Range** 

-65 to +165 deg C

Compliance Certifications (see product page for current document)

**Plotted and Other Data** 

Notes:

C Male Connector Clamp/Solder Attachment for RG59, RG62, RG71 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: C Male Connector Clamp/Solder Attachment for RG59, RG62, RG71 PE4952

URL: https://www.pasternack.com/c-male-standard-rg59-rg62-connector-pe4952-p.aspx


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

# ASSEMBLY PROCEDURES


SLIDE CLAMP NUT (1), WASHER (2) & GASKET (3) OVER CABLE. STRIP CABLE AS SHOWN. DO NOT NICK BRAID WHILE CUTTING JACKET. TAPER END OF BRAID TO PERMIT ASSEMBLY OF BRAID CLAMP (4). SLIDE BRAID CLAMP (4) OVER BRAID & SEAT AGAINST CABLE

[34,8] 1,370



ø [19,1] 0,750

> TO CENTER CONDUCTOR TO DIMENSION SHOWN. DO NOT NICK OVER HEAT DIELECTRIC. INSERT CABLE ASSEMBLY FORM BRAID OVER CLAMP NUT (4). TRIM BRAID BACK TO SHOULDER. CUT DIELECTRIC & CENTER CENTER CONDUCTOR. SOLDER CONTACT TO CENTOCONDUCTOR. REMOVE EXCESS SOLDER. DO NOT & TIGHTEN NTO BODY ö



DWG TITLE

PASTERNACK

53919 FSCM NO.

CAD FILE

061402

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 DIMENSIONS ARE IN INCHES (mm).
 FITS MIL-C-17 AND EQUIVALENT CABLES.

SCALE N/A

XXX

Website: www.pasternack.com | E-Mail: sales@pasternack.com

Phone: (949) 261-1920 | Fax: (949) 261-7451

Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623