

6 dB Fixed Attenuator, 7mm to 7mm Passivated  
Stainless Steel Body Rated to 2 Watts Up to 18 GHz

**PE7023-6**



**Features**

**Applications**

**Description**

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 6 dB Fixed Attenuator PE7023-6 is rated to 2 Watts and operates from DC to 18 GHz. The versatile coaxial package uses 7mm sexless connectors and is also REACH and RoHS compliant.

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Impedance		50		Ohms
Nominal Attenuation		6		dB
VSWR			1.2:1	
Input Power, CW			2	Watts

**Specifications by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 18					GHz
Attenuation Accuracy, Typ	0.3					dB

**Mechanical Specifications**

**Size**

Length	2.13 in [54.1 mm]
Width/Diameter	0.87 in [22.1 mm]
Height	0 in [0 mm]
Weight	0.24 lbs [108.86 g]
Body Material and Plating	Passivated Stainless Steel

**Configuration**

Design	Fixed, Bidirectional
--------	----------------------

## 6 dB Fixed Attenuator, 7mm to 7mm Passivated Stainless Steel Body Rated to 2 Watts Up to 18 GHz



### PE7023-6

#### Connectors

Description	Connector 1	Connector 2
Type	7mm Sexless	7mm Sexless
Connector Specification	IEEE-STD-287	IEEE-STD-287

#### Environmental Specifications

##### Temperature

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

##### Notes:

#### Typical Performance Data

6 dB Fixed Attenuator, 7mm to 7mm Passivated Stainless Steel Body Rated to 2 Watts Up to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [6 dB Fixed Attenuator, 7mm to 7mm Passivated Stainless Steel Body Rated to 2 Watts Up to 18 GHz PE7023-6](#)

URL: <https://www.pasternack.com/6db-fixed-7mm-female-7mm-male-2-watts-attenuator-pe7023-6-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.