



0 to 80 dB Rotary Step Attenuator, BNC Female To BNC
Female With 1 dB Step Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7033-2

Configuration

Design	Step, Bidirectional Attenuator
Connector 1	BNC Female
Connector 2	BNC Female
Body Material and Plating	Aluminum

Electrical Specifications

Frequency Range, GHz	DC to 2
Impedance, Ohms	50
Attenuation Value, dB	0 to 80
Step Size, dB	1
Step Type	Rotary
Maximum Input Power, Watts	1
Maximum VSWR	1.7:1

Frequency 1

Range, MHz	DC to 1,000
Insertion Loss, dB	1
VSWR	1.3:1
Attenuation Accuracy, dB	± 0.5

Frequency 2

Range, GHz	1 to 1.5
VSWR	1.5:1
Attenuation Accuracy, dB	± 0.5

Frequency 3

Range, GHz	1.5 to 2
VSWR	1.7:1
Attenuation Accuracy, dB	± 0.5

Mechanical Specifications

Temperature

Operating Range, deg C	-20 to +85
------------------------	------------

Size

Length, in [mm]	4 [101.6]
Width, in [mm]	5 [127]
Height, in [mm]	4 [101.6]

Connector 1

Type	BNC Female
Outer Conductor Material and Plating	Aluminum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 80 dB Rotary Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 2 GHz PE7033-2](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



0 to 80 dB Rotary Step Attenuator, BNC Female To BNC
Female With 1 dB Step Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7033-2

Connector 2
Type

BNC Female

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes:

Values at 25 °C, sea level

Attenuation Accuracy +/-: 1-10dB 0.5dB, 11-40dB 1.5dB,
41-80dB 2dB

0 to 80 dB Rotary Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 80 dB Rotary Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 2 GHz PE7033-2](http://www.pasternack.com/80db-step-bnc-female-bnc-female-1-watt-attenuator-pe7033-2-p.aspx)

URL: <http://www.pasternack.com/80db-step-bnc-female-bnc-female-1-watt-attenuator-pe7033-2-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.