

20 dB DC Bias Attenuator, N Male to N Female  
Passivated Stainless Steel Body Rated to  
2 Watts from 500 MHz to 2 GHz



## PE7062-20

### Features

### Applications

### Description

### Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	0.5		2	GHz
Impedance		50		Ohms
Attenuation Value		20		dB
Input Power (CW)			2	Watts
VSWR			1.35:1	
Maximum DC Bias Voltage			100	Volts
Maximum DC Bias Current			2	A
Maximum DC Bias Power			100	Watts
Maximum DC Bias Resistance			250	mOhms

### Mechanical Specifications

#### Temperature

Operating Range, deg C -55 to +125

#### Size

Length, in [mm] 2.28 [57.91]  
Width, in [mm] 0.8 [20.32]  
Height, in [mm] 0 [0]  
Weight, lbs [g] 0.151 [68.49]

20 dB DC Bias Attenuator, N Male to N Female  
Passivated Stainless Steel Body Rated to  
2 Watts from 500 MHz to 2 GHz



## PE7062-20

### Configuration:

Design	DC Bias, Bidirectional
Body Material and Plating	Passivated Stainless Steel

### Connectors

Description	Connector 1	Connector 2
Type	N Male	N Female
Specification	MIL-STD-348	MIL-STD-348
Impedance	50 Ohms	
Contact Material & Plating	Beryllium Copper, Gold	Beryllium Copper, Gold
Body Material & Plating	Passivated Stainless Steel	Passivated Stainless Steel
Coupling Nut Material & Plating	Brass, Nickel	
RoHS Compliant	Yes	

### Plotted and Other Data

Notes:  
Values at 25 °C, sea level

### Typical Performance Data

20 dB DC Bias Attenuator, N Male to N Female Passivated Stainless Steel Body Rated to 2 Watts from 500 MHz to 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [20 dB DC Bias Attenuator, N Male to N Female Passivated Stainless Steel Body Rated to 2 Watts from 500 MHz to 2 GHz PE7062-20](#)

URL: <https://www.pasternack.com/20db-dc-bias-n-male-n-female-2-watts-attenuator-pe7062-20-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.