

0 to 40 dB Rotary Continuously Variable Attenuator, SMA Female To SMA Female Rated To 5 Watts From 8 GHz To 12.4 GHz



PE7065-10

Configuration

Design	Continuously Variable, Bidirectional Attenuator
Body Material and Plating	Aluminum

Electrical Specifications Values at 25°C, sea level

Description	Minimum	Typical	Maximum	Units
Frequency Range	8		12.4	GHz
Impedance		50		Ohms
Attenuation Value		40		dB
Step Type		Rotary		
Input Power (CW)			5	Watts
Peak Power			3	kWatts
VSWR			1.7:1	

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Insertion Loss	0.75					dB

Mechanical Specifications

Temperature	
Operating Range	-65 to +125 deg C
Size	
Length	4.5 in [114.3 mm]
Width	4 in [101.6 mm]
Height	4 in [101.6 mm]
Weight	0.838 lbs [380.11 g]

Connectors

Description	Connector 1	Connector 2
Type	SMA Female	SMA Female

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

- Values at 25 °C, sea level

0 to 40 dB Rotary Continuously Variable
Attenuator, SMA Female To SMA Female Rated
To 5 Watts From 8 GHz To 12.4 GHz

PE7065-10



0 to 40 dB Rotary Continuously Variable Attenuator, SMA Female To SMA Female Rated To 5 Watts From 8 GHz To 12.4 GHz from Pasterнак Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0 to 40 dB Rotary Continuously Variable Attenuator, SMA Female To SMA Female Rated To 5 Watts From 8 GHz To 12.4 GHz PE7065-10](https://www.pasterнак.com/40db-continuously-variable-sma-female-sma-female-5-watts-attenuator-pe7065-10-p.aspx)

URL: <https://www.pasterнак.com/40db-continuously-variable-sma-female-sma-female-5-watts-attenuator-pe7065-10-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasterнак Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasterнак Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasterнак Enterprises does not assume liability arising out of the use of any part or document.