



SMA F/M In/Out Bulkhead Coax RF Surge Protector, DC - 5.8GHz, DC Pass, 60 V Max., 10kA, Gas Discharge Tube, BiDirect

RF Surge Protectors Technical Data Sheet

PE73SP1067

Configuration

Input Connector

SMA Female

Output Connector

SMA Male

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

SMA F/M In/Out Bulkhead Coax RF Surge Protector, DC - 5.8GHz, DC Pass, 60 V Max., 10kA, Gas Discharge Tube, BiDirect from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA F/M In/Out Bulkhead Coax RF Surge Protector, DC - 5.8GHz, DC Pass, 60 V Max., 10kA, Gas Discharge Tube, BiDirect PE73SP1067](#)

URL: <https://www.pasternack.com/sma-surge-protector-5.8ghz-gas-discharge-tube-pe73sp1067-p.aspx>

PE73SP1067 CAD Drawing

SMA F/M In/Out Bulkhead Coax RF Surge Protector, DC - 5.8GHz,
DC Pass, 60 V Max., 10kA, Gas Discharge Tube, BiDirect

