

30 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz

PE7423-30



Features

- Directional
- DC to 2.5 GHz Frequency Range
- Attenuation 30±1.5 dB
- Max Power 1 kW (CW)
- VSWR < 1.35:1

Applications

- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems

Description

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 30 dB Fixed Attenuator PE7423-30 is rated to 1000 Watts and operates from DC to 2.5 GHz. The versatile coaxial package uses type N male to type N female connectors and is also REACH and RoHS compliant. The Black Aluminum Heatsink body allows for efficient heat dissipation under high power usage conditions.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.5	GHz
Impedance		50		Ohms
Nominal Attenuation		30		dB
Attenuation Accuracy		1.5		dB
VSWR			1.35:1	
Input Power, CW			1	kWatts
derated linearly to 100W at +125°C				
Input Power, Peak			10	kWatts
5µs pulse, 0.5% duty cycle				

Electrical Specification Notes:

Power sensitivity 0.0001 dB/W max./Temperature coefficient 0.0004 dB/°C max.

Mechanical Specifications

Size

Length	14.8 in [375.92 mm]
Width/Diameter	8.95 in [227.33 mm]
Height	10.27 in [260.86 mm]
Weight	43 lbs [19.5 kg]
Body Material and Plating	Black Aluminum Heatsink

30 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz



PE7423-30

Configuration

Design	Fixed, Directional
Package Style	Connectorized Module

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Female
Connector Specification	MIL-STD-348A	MIL-STD-348A
Coupling Nut Material and Plating	Passivated Stainless Steel	
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Environmental Specification Notes:

Designed to meet MIL-DTL-3933 environmental specifications.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data

30 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [30 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz PE7423-30](#)

URL: <https://www.pasternack.com/30db-fixed-n-male-n-female-1000-watts-attenuator-pe7423-30-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.