

# SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz



# Noise Generators Technical Data Sheet

PE8507

#### **Features**

- 4 to 8 GHz Frequency Range
- Calibrated in 1 GHz Steps
- · High Output ENR 30 to 35 dB
- Flatness ±1 dB

- - SMA Male Output

 +28 VDC Operation SMA Female Voltage Bias

# **Applications**

- Noise Figure Measurements
- Built-In Test Equipment (BITE)
- Automated Test Equipment (ATE)
- Jamming

- Baseband Signal Simulation
- Additive White Gaussian Noise (AWGN) Source for Error Rate Measurements
- SATCOM Bit Error Rate (BER) and Noise Figure Measurements
- Jitter Source

#### Description

The PE8507 is a calibrated noise source module (also known as a noise generator) which operates over a wide frequency range from 4 to 8 GHz. Pasternack's noise source design is calibrated in 1 GHz increments and is ideal for noise figure measurements and a variety of built-in test applications. This noise source model operates at +28 Vdc and features a high output excess noise ratio (ENR) level of 30 to 35 dB. Typical flatness across the entire frequency band is ±1 dB. The package design supports an input SMA female connector for DC biasing, and an output SMA male connector.

#### **Electrical Specifications**

#### **RF Characteristics**

Description	Minimum	Typical	Maximum	Units
Frequency Range	4		8	GHz
Impedance		50		Ohms
Output ENR	30		35	dB
Flatness		±1		dB
Output Variation vs Input Voltage			0.1	dB/%V
Output Variation vs Temperature			0.01	dB/deg C
Bias Voltage 1		28		Volts
Input Current 1		10	25	mA
Rise/Fall Time			1	μs
Calibration Points	1 GHz increments			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz PE8507

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



# SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz



## Noise Generators Technical Data Sheet

PE8507

#### **Mechanical Specifications**

Size

 Length
 2.84 in [72.14 mm]

 Width/Dia.
 0.5 in [12.7 mm]

 Height
 0.5 in [12.7 mm]

 Weight
 0.058 lbs [26.31 g]

Connectors

DC Connector SMA Female
Output Connector SMA Male

**Environmental Specifications** 

**Temperature** 

Operating Range -55 to +85 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

REACH Compliant 12/17/2015

## **Plotted and Other Data**

Notes:

SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz PE8507

URL: https://www.pasternack.com/50-ohm-sma-noise-source-output-32.5-db-4000-mhz-8000-mhz-pe8507-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com

# PE8507 CAD Drawing

SMA Calibrated Noise Source Module, Output ENR of 30 dB, +28 VDC, 4 GHz to 8 GHz

