

1.85mm Jack to 1.85mm Jack 30 Degree Adapter



PE910116

Configuration

- 1.85mm Jack Connector 1
- 1.85mm Jack Connector 2

Features

- Max VSWR of 1.35:1 up to 67 GHz
- Gold Over Nickel-Phosphorus Alloy Over Copper Plated Beryllium Copper Contact

Applications

- General Purpose Test

Description

Pasternack's PE910116 1.85mm jack to 1.85mm jack 30 degree adapter is part of our full line of RF components available for same-day shipping. The 1.85mm connector mates mechanically with commercially available 2.4mm connectors. Our 1.85mm to 1.85mm adapter has a jack to jack gender configuration built of durable stainless steel. PE910116 1.85mm jack to 1.85mm jack adapter operates to 67 GHz. The Pasternack RF adapter provides good VSWR of 1.35:1 maximum. This 30 degree 1.85mm to 1.85mm adapter allows for easier connections in tight spaces.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--------------------------------------|---------|---------|---------|-------|
| Frequency Range | DC | | 67 | GHz |
| Impedance | | 50 | | Ohms |
| VSWR | | | 1.35:1 | |
| Insertion Loss | | | 0.654 | dB |
| Operating Voltage (AC) | | | 150 | Vrms |
| Dielectric Withstanding Voltage (AC) | | | 500 | Vrms |
| Insulation Resistance | 5,000 | | | MOhms |
| RF Leakage | | | 100 | dB |

Mechanical Specifications

Size

| | |
|--------|--------------------|
| Length | 0.92 in [23.29 mm] |
| Width | 0.27 in [6.91 mm] |
| Height | 0.45 in [11.51 mm] |
| Weight | 0.01 lbs [5.31 g] |

1.85mm Jack to 1.85mm Jack 30 Degree Adapter



PE910116

| Description | Connector 1 | Connector 2 |
|--------------------------------------|-------------------------------------|-------------------------------------|
| Polarity | Standard | Standard |
| Mating Cycles, Min | 500 | 500 |
| Mating Torque | 7.08 to 9.74 in-lbs 0.80 to 1.10 Nm | 7.08 to 9.74 in-lbs 0.80 to 1.10 Nm |
| Contact Captivation Axial Force, Min | 4.5 lbs [2.04 kg] | 4.5 lbs [2.04 kg] |
| Coupling Proof Torque | 15 in-lbs [1.7 Nm] | 15 in-lbs [1.7 Nm] |

Material Specifications

| Description | Connector 1 | | Connector 2 | |
|-------------|----------------------------|---|----------------------------|---|
| | Material | Plating | Material | Plating |
| Type | 1.85mm Jack | | 1.85mm Jack | |
| Contact | Beryllium Copper | Gold Over Nickel-Phosphorus Alloy Over Copper | Beryllium Copper | Gold Over Nickel-Phosphorus Alloy Over Copper |
| Insulation | PPO | | PPO | |
| Body | Passivated Stainless Steel | | Passivated Stainless Steel | |

Environmental Specifications

Temperature

Operating Range

-55 to +105 °C

Humidity

MIL-STD-202, Method 206

Thermal Shock

MIL-STD-202, Method 107, Condition B

Salt Spray

MIL-STD-202, Method 101, Condition B

Compliance Certifications (see product page for current document)

Plotted and Other Data

1.85mm Jack to 1.85mm Jack 30 Degree Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1.85mm Jack to 1.85mm Jack 30 Degree Adapter PE910116](#)

URL: <https://www.pasternack.com/1.85mm-jack-to-1.85mm-jack-30-degree-adapter-pe910116.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE910116 CAD Drawing

1.85mm Jack to 1.85mm Jack 30 Degree Adapter

