

SC Male to BNC Female Adapter



TECHNICAL DATA SHEET

PE9200

SC Male to BNC Female Adapter

Configuration

Connector 1 SC Male
Impedance 1 50 Ohms
Connector 2 BNC Female
Impedance 2 50 Ohms
Adapter Design Standard
Body Style Straight

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

Length, in [mm] 1.36 [34.54] Width/Dia., in [mm] 0.8 [20.32]

Connector 1

Type SC Male
Inner Conductor Material and Plating Silver
Inner Conductor Plating Specification QQ-S-365
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Connector 2

Type BNC Female
Inner Conductor Material and Plating Silver
Inner Conductor Plating Specification QQ-S-365
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sc-male-bnc-female-straight-adapter-pe9200-p.aspx

SC Male to BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE9200 CAD Drawing

SC Male to BNC Female Adapter

