



## SMA Male to D-Sub Receptacle Adapter

### TECHNICAL DATA SHEET

PE9424

#### **SMA Male to D-Sub Receptacle Adapter**

Configuration

Connector 1 SMA Male Impedance 1 50 Ohms

Connector 2 D-Sub Receptacle

Impedance 250 OhmsAdapter DesignStandardBody StyleStraight

#### **Mechanical Specifications**

Size

Length, in [mm] 1.604 [40.74] Width/Dia., in [mm] 0.312 [7.92]

**Connector 1** 

Type SMA Male
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Connector 2

Type D-Sub Receptacle

Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

SMA Male to D-Sub Receptacle Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to D-Sub Receptacle Adapter PE9424

URL: http://www.pasternack.com/sma-male-d-sub-receptacle-straight-adapter-pe9424-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

# PE9424 CAD Drawing

SMA Male to D-Sub Receptacle Adapter

