



Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper
from 698 MHz to 2.7 GHz Rated to 300 Watts

RF Tappers Technical Data Sheet

PETP1000

Features

- 2:1 Split (5 dB Coupling)
- Low PIM (-160 dBc)
- 300 watt CW Rating
- 698 to 960 MHz and 1,710 to 2,700 MHz
- VSWR 1.25
- 4.1/9.5 Mini DIN Female Connector
- Mounting Bracket

Applications

- Indoor/Outdoor Use (IP67)
- Base Station
- 4G/LTE/AWS/PCS/PMR/UMTS/TETRA/WiFi/WiMAX
- Distributed Antenna Systems (DAS)
- Wireless Infrastructure

Description

The PETP1000 is a 2:1 Split Ratio Tapper with 4.1/9.5 Mini DIN Female connectors rated to 300 watt CW. Insertion loss is a low 0.17 dB. The Nominal Coupling value at 698 to 960 MHz and 1,710 to 2,700 MHz is 5 dB.

Pasternack's family of Low PIM Power Tappers (Unequal Power Dividers) are designed without solder joints and a unique airline distributed capacitor construction allows for exceptional performance within the 698 to 2,700 MHz frequency range. They are offered in a range of Split Ratios to allow flexibility in the design of your DAS system. Especially designed and manufactured for the rigors of low PIM systems, this family of Tappers is rated at an average power of 300 watt CW, and have PIM performance of -160 dBc or better. They can be used indoor or outdoor as they meet the moisture requirements of IP67. They are available in four different connector types: N, DIN 7-16, 4.3-10, and Mini DIN 4.1/9.5.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.698		2.7	GHz
Split Ratio		2:1		
Impedance		50		Ohms
Coupling		5		dB
Coupling (C1 - C2)		4.8		dB
Coupling (C1 - C3)		1.8		dB
Insertion Loss			0.17	dB
Passive Intermodulation 2 tones at 43 dBm, F1 = 1930 MHz, F2 = 1990 MHz			-160	dBc
Input Power (CW)			300	Watts
Input Power (Peak)			3	kWatts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts PETP1000](#)




Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper
from 698 MHz to 2.7 GHz Rated to 300 Watts

RF Tappers Technical Data Sheet

PETP1000

Performance by Frequency

Description	F1	F2	Units
Frequency Range	698 - 960	1710 - 2700	MHz
Coupling (Tested)	5 ± 0.5	4.9 ± 0.6	dB
Maximum Return Loss (Input Only)	-19	-19	dB



Electrical Specification Notes:

Not designed for use in the 1,500 to 1,690 MHz frequency range.

Mechanical Specifications

Size

Length	4 in [101.6 mm]
Width	1 in [25.4 mm]
Height	2.11 in [53.59 mm]

Weight	0.737 lbs [334.3 g]
--------	---------------------

Housing Material and Plating	Aluminum, Chem Film
------------------------------	---------------------

Configuration

Package Type	Connectorized
Input Connector	4.1/9.5 Mini DIN Female
Output Connector	4.1/9.5 Mini DIN Female
Coupled Connector	4.1/9.5 Mini DIN Female

Environmental Specifications

Humidity	IP67
----------	------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts PETP1000](#)




Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper
from 698 MHz to 2.7 GHz Rated to 300 Watts

RF Tappers Technical Data Sheet

PETP1000

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts PETP1000](#)



Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper
from 698 MHz to 2.7 GHz Rated to 300 Watts

RF Tappers Technical Data Sheet

PETP1000




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts PETP1000](#)



Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper
from 698 MHz to 2.7 GHz Rated to 300 Watts

RF Tappers Technical Data Sheet

PETP1000



Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from 698 MHz to 2.7 GHz Rated to 300 Watts PETP1000](https://www.pasternack.com/low-pim-5db-4.1-9.5-mini-din-unequaltapper-2.7-ghz-300watts-petp1000-p.aspx)

URL: <https://www.pasternack.com/low-pim-5db-4.1-9.5-mini-din-unequaltapper-2.7-ghz-300watts-petp1000-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PETP1000 CAD Drawing

Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from
698 MHz to 2.7 GHz Rated to 300 Watts



TOLERANCES:
HOLE TOLERANCE: X.XXX ±0.003
LENGTH TOLERANCE: X.XXX ±0.010
LENGTH TOLERANCE: X.XX ±0.03

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PETP1000

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

FSCM NO. 53919

CAD FILE 080216


SCALE N/A

SIZE A

2233

PETP1000 CAD Drawing

Low PIM 5 dB 4.1/9.5 Mini DIN Unequal Tapper from
698 MHz to 2.7 GHz Rated to 300 Watts



TOLERANCES:
HOLE TOLERANCE: X.XXX ±.003
LENGTH TOLERANCE: X.XXX ±.010
LENGTH TOLERANCE: X.XX ±.03

PE PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE
PETP1000

FSCM NO. 53919

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE 080216

SCALE N/A

SIZE A

2233