



WR-34 Waveguide Shim, UG-Cover Square flange, 4mm Brass

Waveguide Accessories Technical Data Sheet

PEW34FS4

Features

- WR-34 Waveguide Shim
- Square UG-Cover Flange Configuration
- Frequency Range: 21.7 GHz to 33 GHz
- 4 mm Thick Brass Construction

Description

PEW34FS4 is a WR-34 waveguide shim with operating frequency range from 21.7 GHz to 33 GHz. This waveguide shim is fabricated with 4 mm thick brass by high precision manufacturing process. PEW34FS4 can be used to bridge gaps between WR-34 waveguide components with UG-Cover Square flanges. Pasternack offers wide selection of waveguide components with high performance available in stock and same-day shipping to customers worldwide.

Mechanical Specifications

Body Material	Brass
Body Finish	Gold plating
Length	0.157 in [3.99][mm]
Width	0.874 in [22.2][mm]
Height	0.874 in [22.2][mm]
Weight	0.066 lbs [29.94][g]

Compliance Certifications (see [product page](#) for current document)

WR-34 Waveguide Shim, UG-Cover Square flange, 4mm Brass from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [WR-34 Waveguide Shim, UG-Cover Square flange, 4mm Brass PEW34FS4](#)

URL: <https://www.pasternack.com/pew34fs4-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PEW34FS4 CAD Drawing
WR-34 Waveguide Shim, UG-Cover Square flange, 4mm Brass

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
B	PCR PEW34FS4	6/15/2020	S.PONG



WR-34 WAVEGUIDE
UG-1530/U SQUARE FLANGE



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
.X = ± .2 [5.08] FRACTIONS
.XX = ± .02 [.51] ± 1/32
.XXX = ± .005 [.13] ANGLES ± 1°
CABLE LENGTH (L) TOLERANCES:
L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% L / -0
ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

**PASTERNAK**
an INFINITI® brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 1
SCALE N/A

SIZE A CAGE CODE A 53919 DRAWN BY K.DANG ITEM NO. PEW34FS4 REV B