



WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz

Waveguide to Coax Adapters Technical Data Sheet

PEWCA1008

Features

- X Band
- 8.2 to 12.4 GHz Frequency Range
- WR-90 Waveguide Interface

- Standard UG-39/U Square Cover Flange
- N Female RF Interface

Applications

- Test Benches
- Radar

- Satellite
- Microwave Radio Systems
- Military and Space
- Communication Systems

Description

The PEWCA1008 is a waveguide to coaxial adapter operating in the X Band with a 8.2 to 12.4 GHz frequency range. This adapter offers a WR-90 waveguide interface size using a standard UG-39/U Square Cover Flange. The PEWCA1008 is constructed of Copper Alloy and painted to ensure durability. The coaxial connector offered by this adapter uses a N Female Nickel Plated Brass Connector.

Configuration

Waveguide Size

Flange RF Connector

lara a de la casa

Impedance Body Geometry WR-90

UG-39/U Square Cover

N Female

50 Ohms

Right Angle

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	8.2		12.4	GHz
VSWR		1.25:1		

Mechanical Specifications

Weight 0.3195 lbs [144.92 g]

RF Connector

Connector Type N Female
Body Material and Plating Brass, Nickel

Waveguide Interface

Waveguide Type WR-90
Flange Type Square Cover
Flange Designation UG-39/U
Body Material and Plating Copper Alloy, Paint

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz PEWCA1008

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz



Waveguide to Coax Adapters Technical Data Sheet

PEWCA1008

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

• Values at +25 °C, sea level unless stated otherwise

Typical Performance Data



WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz PEWCA1008

URL: https://www.pasternack.com/wr-90-ug39-square-n-female-waveguide-coax-adapter-12.4-ghz-pewca1008-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

PEWCA1008 CAD Drawing

WR-90 UG-39/U Square Cover Flange to N Female Waveguide to Coax Adapter Operating from 8.2 GHz to 12.4 GHz

