




**NOTICE OF PROPRIETARY RIGHTS** THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA, INCLUDING TRADE SECRETS, PROPRIETARY TO TIMES MICROWAVE SYSTEMS. DISCLOSURE OF THIS DATA IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF TIMES MICROWAVE SYSTEMS.

| SYM | REVISION DESCRIPTION    | DFTM   | DATE    | APPD   | DATE   |
|-----|-------------------------|--------|---------|--------|--------|
| A   | RELEASED FOR PRODUCTION | K.A.M. | 5/20/11 | J.D.B. | 6/9/11 |



Reference standard IEC60169-16

**I. Electric Performance**

Nominal Impedance( $\Omega$ ): 50  
 Frequency Range: DC-6GHz  
 VSWR:  $\leq 1.35$   
 Insert Loss:  $\leq 0.10$  (0-3G)  
 Insulation resistance ( $M\Omega$ ):  $> 5000$   
 Proof voltage (V): 2500  
 Conductor resistance ( $m\Omega$ ):  
 outer conductor  $< 0.4$   
 inner conductor  $< 0.8$

**II. Mechanical Performance**

Whorl pull: 500N  
 Nut torque: 5N.m  
 Tensile force(cable-connect): 300N  
 Torsion(cable-connect): 3N.m

**II. Material and plating :**

| Component       | Material         | Plating                   |
|-----------------|------------------|---------------------------|
| inner conductor | Beryllium copper | Au $>1.27\mu m$           |
| outer conductor | Brass            | Copper-tin-zinc $>2\mu m$ |
| insulator       | PTFE             |                           |
| nut             | Brass            | Copper-tin-zinc $>2\mu m$ |

**III. Environment**


|                  |                                |
|------------------|--------------------------------|
| Temp.range       | -55°C~+155°C                   |
| Thermal shock    | US MIL-STD 202,Meth.107,Cond.B |
| Vibration        | US MIL-STD 202,Meth.204,Cond.B |
| Shock            | US MIL-STD 202,Meth.213,Cond.I |
| Weather standard | IEC 68 55 /155/ 56             |
| ROHS compliant   |                                |

**V. Assemble: inner and outer conductor installed**


|          |                            |                      |                   |   |
|----------|----------------------------|----------------------|-------------------|---|
| MATL:    | UNLESS OTHERWISE SPECIFIED |                      | DFTM: K. A. M.    | TIMES MICROWAVE SYSTEMS                       |
|          | ALL DIMENSIONS ARE IN mm   |                      | DATE: 5/20/11     |   |
| USED ON: |                            |                      | CHKD: J. D. B.    | CONNECTOR, NM<br>FOR LMR-600 (EZ-600-NMC-2-D) |
|          |                            |                      | DATE: 6/9/11      |   |
| SCALE: ~ | DWG. SIZE: A               | DO NOT SCALE DRAWING | APPD: J. D. B.    | SHEET: 1 of 1                                 |
|          |                            |                      | CODE IDENT: 68999 |   |

**NOTICE OF PROPRIETARY RIGHTS** THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA, INCLUDING TRADE SECRETS, PROPRIETARY TO TIMES MICROWAVE SYSTEMS. DISCLOSURE OF THIS DATA IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF TIMES MICROWAVE SYSTEMS.

| SYM | REVISION DESCRIPTION    | DFTM   | DATE    | APPD   | DATE    |
|-----|-------------------------|--------|---------|--------|---------|
| A   | RELEASED FOR PRODUCTION | K.A.M. | 5/23/11 | J.D.B. | 6/9/11  |
| B   | CHANGED PER CDC #37302  | D.J.H. | 3/22/13 | J.D.B. | 3/25/13 |



CABLE PREP.  
USE CST-600  
(3192-052)  
.610" HEX.



Reference Standard IEC60169-4

**I. Electric Performance**

|                                    |  |
|------------------------------------|--|
| Nominal Impedance( $\Omega$ ):     | 50   |
| Frequency Range:                   | DC-3GHz                                      |
| VSWR:                              | $\leq 1.15$                                  |
| Insert Loss(dB):                   | $\leq 0.05$                                  |
| Insulation resistance(M $\Omega$ ) | $\geq 10000$                                 |
| Proof Voltage(V)                   | 2500   |
| Conductor resistance(m $\Omega$ )  | outer conductor <0.2<br>inner conductor <0.8 |

**II. Mechanical Performance**

|                              |       |
|------------------------------|-------|
| Nut Torque                   | 25N.m |
| (Nut)Whorl pull              | 1000N |
| Tensile force(cable-connect) | 500N  |
| Torsion(cable-connect)       | 5N.m  |

**III. Material and plating**

| Component       | Material        | Plating                   |
|-----------------|-----------------|---------------------------|
| Inner conductor | Spring Copper   | Ag 5 $\mu$ m              |
| Outer conductor | Brass           | Copper-tin-zinc 2 $\mu$ m |
| Tube            | Copper          | Copper-tin-zinc 2 $\mu$ m |
| Nut             | Brass           | Nickel 5 $\mu$ m          |
| Gasket          | Silicone Rubber |                           |
| Insulator       | PTFE            |                           |


**IV. Environment**

|                        |                                    |
|------------------------|------------------------------------|
| Temp. range            | -55 $^{\circ}$ C~+155 $^{\circ}$ C |
| Weather standard       | IEC 60068 55 / 155/ 56             |
| Thermal shock          | US MIL-STD 202,Meth.107,Cond.B     |
| Vibration              | US MIL-STD 202,Meth.204,Cond.B     |
| Shock                  | US MIL-STD 202,Meth.213,Cond.I     |
| Waterproofing standard | IP68                               |
| ROHS Compliant         |                                    |


V. Assembly: inner conductor installed and outer conductor crimped

|              |   |                |   |
|--------------|---|----------------|---|
| MATL:        | UNLESS OTHERWISE SPECIFIED  | DFTM. K. A. M. | TIMES MICROWAVE SYSTEMS   |
|              | ALL DIMENSIONS ARE IN mm<br>MACHINED SURFACES FINISH N/A RMS MAX.<br>REMOVE ALL BURRS N/A MAX. BREAK<br>MACHINE CORNERS N/A MAX. FILLET R.<br>TOLERANCES ON DECIMALS<br>.XX $\pm$ N/A .XXX $\pm$ N/A<br>ANGLES $\pm$ 1 $^{\circ}$ FRACTIONS $\pm$ N/A | DATE 5/23/11   |   |
| USED ON: 0-0 | DO NOT SCALE DRAWING  | CHKD. J. D. B. | <b>EZ-600-716M-X</b><br>7-16 MALE FOR LMR-600 CABLE<br>EZ/CRIMP/NO BRAID TRIM |
|              |   | DATE 6/9/11    |   |
| SCALE: N/A   | DWG. SIZE A   | APPD. J. D. B. | SHEET 1 of 1 SD3190-2643 REV B  |
|              | CODE IDENT 68999  | DATE 6/9/11    |   |


# Installation Instruction




1. A. Trim cable to dimensions shown. Be careful to avoid nicking the braid  
B. Remove any residual plastic from center conductor  
C. Deburr center conductor using a fine file or Times DBT-U tools  
D. Avoid nicking aluminum tape or center conductor



2. A. Slide crimp ferrule and heat shrink tube over the cable  
B. Flare the braid



3. A. Insert Cable into connector body until dielectric is seated and center conductor is inserted fully into connector center pin.



4. A. Slide crimp ferrule over braid and crimp as close to body as possible using .429" HEX crimp tooling. Pay attention to the crimp area, do not crimp rear of crimp sleeve  
B. Heat shrink tube over rear of connector body and down on to cable jacket using hot air gun

# LMR<sup>®</sup>-600 Flexible Low Loss Communications Coax

## Ideal for...

- Jumper Assemblies in Wireless Communications Systems
- Short Antenna Feeder runs
- Any application (e.g. WLL, GPS, LMR, WLAN, WISP, WiMax, SCADA, Mobile Antennas) requiring an easily routed, low loss RF cable



• **LMR<sup>®</sup>** standard is a UV Resistant Polyethylene jacketed cable designed for 20-year service outdoor use. The bending and handling characteristics are significantly better than air-dielectric and corrugated hard-line cables.

• **LMR<sup>®</sup>-DB** is identical to standard LMR plus has the advantage of being watertight. The addition of waterproofing compound in and around the foil/braid insures continuous reliable service should the jacket be inadvertently damaged during installation or in the future.

• **LMR<sup>®</sup>-FR** is a non-halogen (non-toxic), low smoke, fire retardant cable designed for in-building runs that can be routed anywhere except air handling plenums. LMR-FR is UL/NEC & CSA rated 'CMR' and 'FT4' respectively, meets FAA FAR25 requirements and is MSHA-P for mining applications.

• **LMR<sup>®</sup>-FR-PVC** is a general-purpose indoor cable and has a UL/NEC & CSA rating of 'CMR' and 'FT4' respectively. It is less expensive than LMR-FR, however it emits toxic fumes (HCL) and greater smoke density when burned.

• **LMR<sup>®</sup>-PVC** is designed for low loss general-purpose applications and is somewhat more flexible than the standard polyethylene jacketed LMR.

• **LMR<sup>®</sup>-PVC-W** is a white-jacketed version of LMR-PVC for marine and other applications where color compatibility is desired.

• **Flexibility** and bendability are hallmarks of the LMR-600 cable design. The flexible outer conductor enables the tightest bend radius available for any cable of similar size and performance.

• **Low Loss** is another hallmark feature of LMR-600.

Size for size LMR has the lowest loss of any flexible cable and comparable loss to semirigid hard-line cables.

• **RF Shielding** is 50 dB greater than typical single shielded coax (40 dB). The multi-ply bonded foil outer conductor is rated conservatively at > 90 dB (i.e. >180 dB between two adjacent cables).

• **Weatherability:** LMR-600 cables designed for outdoor exposure incorporate the best materials for UV resistance and have life expectancy in excess of 20 years.

• **Connectors:** A wide variety of connectors are available for LMR-600 cable, including all common interface types, reverse polarity, and a choice of solder or non-solder center pins. Most LMR connectors employ crimp outer attachment using standard hex crimp sizes.

• **Cable Assemblies:** All LMR-600 cable types are available as pre-terminated cable assemblies. Refer to the section on FlexTech for further details.

| Part Description |                      |              |       | Stock |       |
|------------------|----------------------|--------------|-------|-------|-------|
| Part Number      | Application          | Jacket Color | Code  |       |       |
| LMR-600          | Outdoor              | PE           | Black | 54003 |       |
| LMR-600-DB       | Outdoor/Watertight   | PE           | Black | 54093 |       |
| LMR-600-FR       | Indoor/Outdoor Riser | CMR          | FRPE  | Black | 54032 |
| LMR-600-FR-PVC   | Indoor/Outdoor Riser | CMR          | FRPVC | Black | 54074 |
| LMR-600-PVC      | General Purpose      | PVC          | Black | 54219 |       |
| LMR-600-PVC-W    | General Purpose      | PVC          | White | 54206 |       |


| Construction Specifications |                   |       |         |
|-----------------------------|-------------------|-------|---------|
| Description                 | Material          | In.   | (mm)    |
| Inner Conductor             | Solid BCCAI       | 0.176 | (4.47)  |
| Dielectric                  | Foam PE           | 0.455 | (11.56) |
| Outer Conductor             | Aluminum Tape     | 0.461 | (11.71) |
| Overall Braid               | Tinned Copper     | 0.490 | (12.45) |
| Jacket                      | (see table above) | 0.590 | (14.99) |

| Mechanical Specifications |                |       |          |
|---------------------------|----------------|-------|----------|
| Performance Property      | Units          | US    | (metric) |
| Bend Radius: installation | in. (mm)       | 1.50  | (38.1)   |
| Bend Radius: repeated     | in. (mm)       | 6.0   | (152.4)  |
| Bending Moment            | ft-lb (N-m)    | 2.75  | (3.73)   |
| Weight                    | lb/ft (kg/m)   | 0.131 | (0.20)   |
| Tensile Strength          | lb (kg)        | 350   | (158.9)  |
| Flat Plate Crush          | lb/in. (kg/mm) | 60    | (1.07)   |

| Environmental Specifications   |          |         |
|--------------------------------|----------|---------|
| Performance Property           | °F       | °C      |
| Installation Temperature Range | -40/+185 | -40/+85 |
| Storage Temperature Range      | -94/+185 | -70/+85 |
| Operating Temperature Range    | -40/+185 | -40/+85 |

| Electrical Specifications |                   |       |          |
|---------------------------|-------------------|-------|----------|
| Performance Property      | Units             | US    | (metric) |
| Velocity of Propagation   | %                 | 87    |          |
| Dielectric Constant       | NA                | 1.32  |          |
| Time Delay                | nS/ft (nS/m)      | 1.17  | (3.83)   |
| Impedance                 | ohms              | 50    |          |
| Capacitance               | pF/ft (pF/m)      | 23.4  | (76.6)   |
| Inductance                | uH/ft (uH/m)      | 0.058 | (0.19)   |
| Shielding Effectiveness   | dB                | >90   |          |
| DC Resistance             |                   |       |          |
| Inner Conductor           | ohms/1000ft (/km) | 0.53  | (1.7)    |
| Outer Conductor           | ohms/1000ft (/km) | 1.2   | (3.9)    |
| Voltage Withstand         | Volts DC          | 4000  |          |
| Jacket Spark              | Volts RMS         | 8000  |          |
| Peak Power                | kW                | 40    |          |

**Attenuation vs. Frequency (typical)**



| Frequency (MHz)              | 30   | 50   | 150  | 220  | 450  | 900  | 1500 | 1800 | 2000 | 2500 | 5800 |
|------------------------------|------|------|------|------|------|------|------|------|------|------|------|
| <b>Attenuation dB/100 ft</b> | 0.4  | 0.5  | 1.0  | 1.2  | 1.7  | 2.5  | 3.3  | 3.7  | 3.9  | 4.4  | 7.3  |
| <b>Attenuation dB/100 m</b>  | 1.4  | 1.8  | 3.2  | 3.9  | 5.6  | 8.2  | 10.9 | 12.1 | 12.8 | 14.5 | 23.8 |
| <b>Avg. Power kW</b>         | 5.51 | 4.24 | 2.41 | 1.97 | 1.35 | 0.93 | 0.70 | 0.63 | 0.59 | 0.52 | 0.32 |

**Calculate Attenuation =**  
 $(0.075550) \cdot \sqrt{\text{FMHz}} + (0.000260) \cdot \text{FMHz}$  (interactive calculator available at [http://www.timesmicrowave.com/cable\\_calculators](http://www.timesmicrowave.com/cable_calculators))

**Attenuation:**  
 VSWR=1.0; Ambient = +25°C (77°F)

**Power:**  
 VSWR=1.0; Ambient = +40°C; Inner Conductor = 100°C (212°F); Sea Level; dry air; atmospheric pressure; no solar loading

# LMR®-600 Flexible Low Loss Communications Coax



## Connectors

| Interface       | Description      | Part Number      | Stock Code | VSWR**  | Coupling Freq. (GHz) | Nut       | Inner Contact Attach | Outer Contact Attach | Finish* Body /Pin | Length in (mm) | Width in (mm) | Weight lb (g) |
|-----------------|------------------|------------------|------------|---------|----------------------|-----------|----------------------|----------------------|-------------------|----------------|---------------|---------------|
| 7/8 EIA         | Flange           | EZ-600-78EIA     | 3190-1373  | <1.25:1 | (2.5)                | NA        | Spring Finger        | Clamp                | S/S               | 2.3 (58)       | 2.60 (66.0)   | 0.873 (396.0) |
| 7-16 DIN Female | Straight Jack    | TC-600-716FC     | 3190-375   | <1.25:1 | (2.5)                | NA        | Solder               | Clamp                | S/S               | 1.1 (28)       | 1.00 (25.4)   | 0.249 (112.9) |
| 7-16 DIN Male   | Straight Plug    | EZ-600-716MH     | 3190-503   | <1.25:1 | (2.5)                | Hex       | Spring Finger        | Crimp                | S/S               | 2.0 (51)       | 1.30 (33.0)   | 0.254 (115.2) |
|                 | Straight Plug    | TC-600-716MC     | 3190-502   | <1.25:1 | (2.5)                | Hex       | Solder               | Clamp                | S/S               | 2.0 (51)       | 1.30 (33.0)   | 0.347 (157.4) |
|                 | Right Angle      | TC-600-716M-RA   | 3190-395   | <1.35:1 | (2.5)                | Hex       | Solder               | Crimp                | S/S               | 1.4 (36)       | 1.40 (35.6)   | 0.354 (160.8) |
| 7/16 Male       | Right Angle      | EZ-600-716M-RA-X | 3190-2546  | <1.35:1 | (6)                  | Hex       | Spring Finger        | Crimp                | A/G               | 1.6 (40)       | 1.38 (35.0)   | 0.462 (210.0) |
|                 | Straight Jack    | EZ-600-716F      | 3190-2447  | <1.25:1 | (6)                  | Hex       | Spring Finger        | Crimp                | A/G               | 1.8 (45)       | 1.32 (33.6)   | 0.158 (71.7)  |
| HN Male         | Straight Plug    | TC-600-HNM       | 3190-1429  | <1.25:1 | (<1)                 | Knurl     | Solder               | Clamp                | S/G               | 2.3 (59.2)     | 0.88 (22.4)   | 0.25 (113)    |
| LC Male         | Straight Plug    | TC-600-LCM       | 3190-1406  | <1.25:1 | (<1)                 | Hex       | Solder               | Clamp                | N/S               | 3.1 (78.0)     | 1.62 (41.1)   | 1.20 (544)    |
| N Female        | Straight Jack    | EZ-600-NF        | 3190-955   | <1.25:1 | (2.5)                | NA        | Spring Finger        | Crimp                | S/G               | 2.3 (59)       | 0.87 (22.1)   | 0.150 (68.0)  |
|                 | Bulkhead Jack    | EZ-600-NF-BH     | 3190-616   | <1.25:1 | (2.5)                | NA        | Spring Finger        | Crimp                | S/G               | 2.4 (61)       | 0.88 (22.4)   | 0.195 (88.5)  |
|                 | Bulkhead Jack    | TC-600-NF-BH     | 3190-589*  | <1.25:1 | (2.5)                | NA        | Solder               | Crimp                | S/G               | 2.4 (61)       | 0.88 (22.4)   | 0.195 (88.5)  |
|                 | Bulkhead Jack    | TC-600-NFC-BH    | 3190-466   | <1.25:1 | (2.5)                | NA        | Solder               | Clamp                | S/G               | 2.2 (56)       | 0.94 (23.9)   | 0.214 (97.1)  |
| N Male          | Straight Plug    | EZ-600-NMK       | 3190-669   | <1.25:1 | (2.5)                | Knurl     | Spring Finger        | Crimp                | S/G               | 2.1 (53)       | 0.92 (23.4)   | 0.164 (74.4)  |
|                 | Straight Plug    | EZ-600-NMC-2     | 3190-2641  | <1.25:1 | (6)                  | Hex/Knurl | Spring Finger        | Clamp                | A/G               | 2.1 (53)       | 0.92 (23.4)   | 0.202 (91.6)  |
|                 | Straight Plug    | TC-600-NMC       | 3190-357*  | <1.25:1 | (2.5)                | Hex       | Solder               | Clamp                | S/G               | 2.1 (53)       | 0.92 (23.4)   | 0.208 (93.4)  |
|                 | Straight Plug    | EZ-600-NMH-X     | 3190-2627  | <1.25:1 | (8)                  | Hex/Knurl | Spring Finger        | Crimp                | A/G               | 2.1 (53)       | 0.92 (23.4)   | 0.164 (74.4)  |
|                 | Straight Plug    | TC-600-NMH-X     | 3190-2628  | <1.25:1 | (8)                  | Hex/Knurl | Spring Finger        | Crimp                | A/G               | 2.1 (53)       | 0.92 (23.4)   | 0.166 (75.3)  |
|                 | Right Angle      | EZ-600-NMH-RA-X  | 3190-2639  | <1.35:1 | (6)                  | Hex       | Spring Finger        | Crimp                | A/G               | 2.0 (50)       | 1.42 (36.0)   | 0.224 (101.7) |
|                 | Right Angle      | TC-600-NMH-RA-D  | 3190-2427  | <1.35:1 | (6)                  | Hex       | Solder               | Crimp                | A/G               | 1.8 (46.5)     | 1.62 (41.2)   | 0.208 (93.4)  |
| QDS Male        | Straight Plug    | TC-600-QDSM      | 3190-846   | <1.25:1 | (<1)                 | Knurl     | Solder               | Clamp                | A/G               | 2.2 (55.6)     | 1.00 (25.4)   | 0.25 (113)    |
|                 | Right Angle      | TC-600-QDSM-RA   | 3190-847   | <1.25:1 | (<1)                 | Knurl     | Solder               | Clamp                | A/G               | 2.4 (61.5)     | 1.88 (47.8)   | 0.35 (159)    |
| TNC Male        | Straight Plug    | TC-600-TM-X      | 3190-2530  | <1.25:1 | (6)                  | Hex/Knurl | Solder               | Crimp                | A/G               | 2.3 (57.6)     | 0.75 (19.0)   | 0.100 (45.6)  |
|                 | Straight Plug    | EZ-600-TM-X      | 3190-2531  | <1.25:1 | (6)                  | Hex/Knurl | Spring Finger        | Crimp                | A/G               | 2.3 (57.6)     | 0.75 (19.0)   | 0.100 (45.6)  |
|                 | Reverse Polarity | EZ-600-TM-RP     | 3190-796   | <1.25:1 | (2.5)                | Knurl     | Spring Finger        | Crimp                | A/G               | 2.2 (56)       | 0.87 (22.0)   | 0.112 (50.8)  |
| TNC Female      | Reverse Polarity | EZ-600-TF-RP     | 3190-797   | <1.25:1 | (2.5)                | NA        | Spring Finger        | Crimp                | A/G               | 2.3 (58)       | 0.87 (22.0)   | 0.100 (45.4)  |
| UHF Male        | Straight Plug    | EZ-600-UM        | 3190-615   | <1.25:1 | (2.5)                | Knurl     | Spring Finger        | Crimp                | S/G               | 1.7 (43)       | 0.88 (22.4)   | 0.164 (74.4)  |
|                 | STRAIGHT PLUG    | TC-600-UMC       | 3190-213   | <1.25:1 | (2.5)                | KNURL     | SOLDER               | CLAMP                | S/G               | 1.7 (43)       | 0.88 (22.4)   | 0.198 (89.8)  |

Finish metals: N=Nickel, S=Silver, G=Gold, SS=Stainless Steel, A=Alloy \*\*VSWR spec based on 3 foot cable with a connector pair \*Available in bulk pack



**Install Tools**

| Type               | Part Number | Stock Code | Description   |
|--------------------|-------------|------------|---|
| Crimp Tool         | HX-4        | 3190-200   | Crimp Handle  |
| Crimp Dies         | Y1720       | 3190-203   | .610" Hex Dies  |
| Crimp Rings        | CR-600      | 3190-831   | Crimp Rings for TC/EZ-600 connectors (pkg of 10)  |
| Strip Tool         | CST-600     | 3192-052   | Combination prep tool for LMR-600 crimp and clamp style connectors                          |
| Replacement Blades | RB-456      | 3190-421   | Replacement Blades for Strip Tools  |
| Deburr Tool        | DBT-U       | 3192-001   | Removes center conductor rough edges  |
| Midspan Strip Tool | GST-600A    | 3190-1051  | For ground strap attachment   |
| Wrench             | WR600       | 3190-1435  | 15/16" Box Wrench (2 required for EZ-600-NMC-2)   |
| Cutting Tool       | CCT-01      | 3190-1544  | Cable end flush cut tool  |
| Replacement Blade  | RB-01       | 3190-1609  | Replacement blade for cutting tool  |
| Replacement Blade  | RB-CST      | 3192-086   | Replacement blade kit for all CST strip tools   |
| Tool Kit           | TK-600EZ    | 3190-1602  | Tool kit for LMR crimp/clamp connectors (includes CCT-01, CST-600, HX-4, Y1720, Tool Pouch) |



**Hardware Accessories**

| Type                             | Part Number | Stock Code | Description  |
|----------------------------------|-------------|------------|--|
| Ground Kit                       | GK-S600TT   | GK-S600TT  | Standard Grounding Kit (each)                              |
| Hoisting Grip                    | HG-600T     | HG-600T    | Split/Laced Type (each)                                    |
| Cold Shrink                      | CS-A600T    | CS-A600T   | Cable to Antenna Junction (each)                           |
| Cold Shrink                      | CS-60120T   | CS-60120T  | LMR-600 to -1200 Junction (each)                           |
| Cold Shrink                      | CS-60170T   | CS-60170T  | LMR-600 to -1700 Junction (each)                           |
| Hanger Blocks                    | CB-600T     | CB-600T    | Dual Cable Support Block (kit of 10)                       |
| Standard Entry                   |             |            |  |
| Port Cushion                     | SC-600T-3   | SC-600T-3  | Three cables (each)  |
| Snap-In Hangers                  | SH-U600T    | SH-U600T   | Snap-In Hangers (Kit of 10)                                |
| Hanger Block Supporting Hardware |             |            | Complete Range of Supporting Hardware & Adapters Available |